

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Cities Service Oil and Gas Corporation		7. Unit Agreement Name
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		8. Farm or Lease Name Byers B
4. Location of Well UNIT LETTER <u>H</u> <u>2080</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>7</u> TOWNSHIP <u>20S</u> RANGE <u>38E</u> N.M.P.M.		9. Well No. 1
15. Elevation (Show whether DF, RT, GR, etc.) 3566' GR		10. Field and Pool, or Whichever Nadine Drinkard, West
12. County Lea		

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
TD 7100' Dolomite & Lime. Waiting on Completion Unit. Drilled a 7-7/8" hole to a TD of 7100' in Dolomite & Lime. Ran and set 19 jts. (1070.92') 5-1/2" OD 17# K55, 16 Jts. (634.26') 5-1/2" OD 15.5# K55 and 120 jts (5232.80') 5-1/2" OD 14# K55 casing @ 6650' and cemented with 924 sacks of Halco Lite w/16.5# salt, 3# gilsonite & 1/4# Flocele/sack + 425 sacks of Class C w/5# salt and 23% Halad 4/sack of cement. When cement started out of shoe, picked up casing to 6650' spotting a 10' cement plug below casing @ 6660-6650'. PD @ 0705 MDT on 10-15-83. Circulated 200 sacks to pits. Set slips, CO casing, ND BOP's and NU Wellhead.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bart C. Zimmerman

TITLE Region Petroleum Engineer

DATE 10-17-83

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

OCT 21 1983

RECEIVED

OCT 20 1983

O.C.D.
HOBBS OFFICE