

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fed <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - FORM C-101 FOR SUCH PROPOSALS.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Cities Service Oil and Gas Corporation		8. Farm or Lease Name Byers B
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>2080</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>7</u> TOWNSHIP <u>20S</u> RANGE <u>38E</u> N.M.P.M.		10. Field and Pool, or Wildcat Nadine Drinkard, West
15. Elevation (Show whether DF, RT, GR, etc.) 3566' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 1550' Red Beds. Prep to drill ahead. MIRU rotary and spudded a 12-1/4" hole @ 1700 MDT on 9-26-83 and drilled to a T.D. of 1550' in Red Beds. Ran and set 37 Jts. (1532.43') of 8-5/8" OD 24# K-55 casing @ 1547' and cemented w/600 sacks of Class C w/4% Gel, 3.7# salt and 1/4# Flocele/sack + 200 sacks of Class C w/2% Gel cement. PD @ 0836 MDT on 9-28-83. Cement circulated to surface. WOC 18 hrs. Tested blind rams and casing to 1500# for 30 min. - Held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Elmer Startz</u>	TITLE <u>Region Opr. Mgr. - Prod.</u>	DATE <u>October 4, 1983</u>
ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR		
APPROVED BY _____	TITLE _____	DATE <u>OCT 6 1983</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

OCT 5 1983

O.C.D.
HOBBS OFFICE