STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

60. 07 68*180 06661968	I	
DISTRIBUTION		
BANTA FE		
PILE "		[.
U.S.O.S.		
LAND OFFICE		
OPERATOR	T^{-}	

CONDITIONS OF APPROVAL, IF ANY

OIL CONSERVATION DIVISION P. O. BOX 2088

Form C-103

SANTA FE, NEW MEXICO 87501	Revised 10-1-78
PILE "	5a, Indicate Type of Lease
U.S.O.S.	
LAND OFFICE	State Fee XX
OPERATOR	5, State Oil 6 Gas Lease No.
	mmmmmm
SUNDRY NOTICES AND REPORTS ON WELLS	
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. - OIL GAO	7. Unit Agreement Name
WELL & WELL OTHER-	0.52
1. Name of Operator Exact C. Vator. The	8, Form or Lease Name
Fred G. Yates, Inc.	Amoco "12" 9. Well No.
3. Address of Operator	1
Sunwest Centre, Suite 919, Roswell, NM 88201	10 5014
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER D . 660 PEET FROM THE NORTH LINE AND 660 FEET FROM	Undesignated
·	
THE WEST LINE, SECTION 12 TOWNSHIP 20S RANGE 38E NAMED.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3566' G.L.	Lea
Check Appropriate Box To Indicate Nature of Notice, Report or Otl	her Data
· · ·	REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB	
OTHER Re-cement casing	kx3
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703.	estimated date of starting any proposed
2/13/85: Ran Gamma Ray Correlation Collar Log & Bond Log. Log showed no	honding up to 7056! good
bond at 7003', improving to 100% bond at 6966'. Requires recementing	onnocito Drinkard nov
at 7059'-7060'.	g opposite brinkard pay
2/14/85: RIH w/4 shot casing gun. Perforate 7155'-7156' for cement circu	lating ich outgide essine
to return through perfs 7059'-7060'. Mixed & displaced 37 sxs Class	""" coment vi/veter less
control additive. Closed annulus. Squeezed 1 barrel cement at 1500	
well w/braiden head "squeeze". Held pressure on same 1 hour. Cement	in place UCC at 6:00
p.m. 2/14/85.	in place, woc at 6:00
2/15/85: Drilled out cement from 6998'-7060'; reverse circulated tubing	realisms was into soment
at 7075'. Drilled to top of retainer at 7132'.	volume, ran into cement
2/16/85 - 2/17/85: Shut down for weekend.	
2/18/85: RU Dresser & re-ran Bond Correlation Collar Log. Bottom of hole	shup off has seed to
2/10/05: RU Diesser & re-lan Bond Correlation Collar Log. Bottom of note	'Off anti-
excellent bonding from 7071' down. Perforated 7010'-7026' w/2 SPF,	.40# entry noie.
Acidized well and began swabbing.	
	•
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
$\Omega D D D D -$	
augus Mary Markenn rice Engineer	DATE 2/21/85
The state of the s	
ORIGINAL SIGNED BY JERRY SEXTON	FEB 2 5 1985

RECEIVED

FEB 22 1985

O.C.D.