

COMPLETIONS
PI# 30-T-0037 02/10/86 SEC 2 TWP 22S RGE 35E
30-025-29419-0000 PAGE 3

MAGNATEX PET
1 NORTH LAKE D DO

DRILLING PROGRESS DETAILS

09/17 915-682-5263
11/07 LOC/1985/
11/14 415 TD, WOC
11/18 DRLG 3850
11/25 4000 TD, WOCT
12/09 4000 TD, SWBG
12/16 4000 TD, MICT
01/08 4000 TD, PREP POP
02/05 TD REACHED 4000 TD, PB 3939, TOP
11/12/85 RIG REL 11/15/85
COMP 1/4/86, IPP 16 BO, 3 MCFGPD, 3 BWPB,
GTY 37.2, GOR 188
PROD ZONE - YATES 3867-3910
NO CORES OR DSTS RPTD

WRS COMPLETION REPORT

COMPLETIONS SEC 2 TWP 22S RGE 35E
PI# 30-T-0037 02/10/86 30-025-29419-0000 PAGE 1

NMEX LEA * 1980FSL 1980FWL SEC
STATE COUNTY FOOTAGE
MAGNATEX PET D DO
OPERATOR WELL CLASS N.T. PERM.
1 NORTH LAKE
WELL NO. LEASE NAME
3575GR JALMAT
OPER. ELEV. FIELD - POOL AREA
API 30-025-29419-0000

LEASE TYPE NO. PERMIT OR WELL ID NO.
11/06/1985 01/04/1986 ROTARY OIL
SPUD DATE COMP. DATE TYPE TOOL STATUS
4000 YATES RHYMES DRLG 4
PROJ. DEPTH- FORM CONTRACTOR
DTD 4000 PB 3939 FM/TD YATES
DRILLERS TD LOG TD PLUG BACK TD OLD TD FORM TD

LOCATION DESCRIPTION

7 MI SW OIL CENTER, NM

CASING/LINER DATA

CSG 8 5/8 @ 415 W/ 300 SACKS 01
CSG 4 1/2 @ 4000 W/ 530 SACKS 02

TUBING DATA

TBG 2 3/8 AT 3880

INITIAL POTENTIAL

IPP 16BOPD 3.0MCFD 3BW
YATES PERF W/ 2/FT 3400- 3939 007
PERF 3400- 3939
GTY 37.2 GOR 188

TYPE	FORMATION	LTH	TOP	DEPTH/SUB	BSE	DEPTH/SUB
LOG	RUSTLER		1855	1720		
LOG	SALT				3600	-25
LOG	YATES		3798	-223		

PRODUCTION TEST DATA

YATES PERF W/ 2/FT 3867- 3910 GROSS 003
PERF 3867- 3871 3882- 3888 3900- 3910
ACID 3867- 3910 2750GALS

CONTINUED IC# 300257046685

Copyrighted
Reproduction
Prohibited



Petroleum Information
CORPORATION

1-800-955-0000

COMPLETIONS SEC 2 TWP 22S RGE 35E
P1# 30-T-0037 02/10/86 30-025-29419-0000 PAGE 2

MAGNATEX PET NORTH LAKE D DC
1

PRODUCTION TEST DATA

750 GALS 15% HCL
2000 GALS 3% HE, 12% HCL
SWBD 16 BLW W/TR OIL

YATES PERF 3867- 3910 004
SFFR 3867- 3910 26000GALS 40200LBS SAND
70% FOAM 20/40 SD
SWBD 54 BLW W/TR OIL IN 5 1/2 HRS

YATES PERF W/ 2/FT 3400- 3939 005
PERF 3400- 3939
ACID 3400- 3939 500GALS
15% HCL 2000 GALS (3% HF & 12% HCL)
250 GALS (15% HCL + 2% KCL WTR)
SWBD 16 BLW IN 2 HRS

YATES PERF 3400- 3939 006
SFFR 3400- 3939 26800GALS 40200LBS SAND
70% FOAM 20/40 SD
FLWD 54 BLW W/TR OIL IN 5 HRS 30 MINS THRU 12/64 CK

PTS 3BO 3HRS
YATES PERF 3400- 3939 007
PERF 3400- 3939
ACID 3400- 3939 2700GALS
BRPG 3400- 3939 100 SCF NTGN PER BBL
SWBD 3 BO - 28 BLW DEPTH 3939

PTP 3BOPD 3BW
YATES PERF 3867- 3910 008
PERF 3867- 3910

LOGS AND SURVEYS /INTERVAL,TYPE/

LOGS DIL CNDL

DRILLING PROGRESS DETAILS

MAGNATEX PET
405 ONE MARIENFELD PLACE
MIDLAND, TX 79701

CONTINUED