

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) Notice Complete I		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Midland, Texas

February 16, 1959

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

The Texas Company

G. H. Weir "A"

Well No. **4** in **E**

SW **NW** (Company or Operator) **IX** **20-8** **37/8"** **Shaggs Drinkard** (Unit)
1/4 (40-acre Subdivision) 1/4 of Sec. T. R. NMPM. Pool
San County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TO INCREASE PRODUCTION WE PROPOSE TO DO THE FOLLOWING:

1. Kill well with salt water.
2. Perforate 5 1/2" casing from 5240' to 5263' with 4 jet shots per foot.
3. Set Baker Retrievable bridge plug at 5350'.
4. Wash perforations 5240' to 5263' with 500 gallons of 15% regular acid.
5. Swab and test Glorietta (Per. 5240' to 5263').
6. If necessary, fracture perforations 5240' to 5263' with 5000 gallons refined oil and 5000 pounds of sand.
7. Swab and Test.
8. Set Baker Model "D" Production packer with latch down device at 6800' and run dual strings of 2 1/16" O.D. Hydrill tubing with parallel latching sub on long string.
9. Test and place both zones on production.

February 16

59

Approved....., 19.....
Except as follows:

The Texas Company

Company or Operator

By **J. G. Mlevins, Jr.**
Position **Assistant District Supt.**

Send Communications regarding well to:

J. G. Mlevins, Jr.

Name

Address **P.O. Box 352, Midland, Texas**

Approved
OIL CONSERVATION COMMISSION

By **[Signature]**

Title