

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.O.B.		
LAND OFFICE		
OPERATOR		

3a. Indicate Type of Lease
State ☐ Fee ☒
3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Chevron U.S.A. Inc.	8. Form or Lease Name H. T. Mattern (NCT-)B
3. Address of Operator P.O. BOX 670, Hobbs, NM 88240	9. Well No. 24
4. Location of Well UNIT LETTER <u>B</u> <u>850</u> FEET FROM THE <u>North</u> LINE AND <u>1725</u> FEET FROM THE <u>East</u> LINE, SECTION <u>31</u> TOWNSHIP <u>21S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or WHdcat Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) 3485	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/2/87 Run 5 1/2" casing to 6800, Pmp 100 sx Class C lead slurry, tail w/ 800 sx Class C, displaced w/80bbl water, did not bump plug. circ out 226 sx good slurry, circ between stages, Mix and pump 400 sx Class C and tail w/ 200 sx Class C neat. Circ. 97 sx good slurry to pits, make final cut, install tbg spool, bonnet, tst void to 3000psi for 20 min. , no leak off. Wait on completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CREATED BY <u>M. E. Akins</u>	TITLE <u>Staff Drilling Engineer</u>	DATE <u>August 4, 1987</u>
ORIGINAL SIGNED BY JERRY SEXTON		
DISTRICT 1 SUPERVISOR		
CONDITIONS OF APPROVAL, IF ANY:		
		DATE <u>AUG 10 1987</u>