

MAXUS EXPLORATION COMPANY

FEDERAL 24-34 #1

LEA COUNTY, NEW MEXICO

ITEM #29 CASING RECORD & CEMENTING REPORT

13 3/8" 19 Jts K-55 54.5#, 48#, 68# Set @ 750' w/850 sx of premium plus cement w/2% CC and #/sk flocele.

10 34/" 35 Jts S-95 55.5# ST&C Set @ 4746.80' w/600 sx HLC
67 Jts K-55 45.5# ST&C w/15#/sk salt and #/sk flocele.
10 Jts J-55 45.5# ST&C Tail in w/200 sx Class "C" w/2% CC. DV tool at 1788'.

Second Stage: 310 sx HLC w/15#/sk salt, #bbl flocele and 200 sx Class "C" w/2% CC. Circulate 15 sx at surface.

7 5/8" 269 Jts N-80 39" LT&C Set @ 11,692' w/600 sx Class "H" w/0.5% CFR-2, 0.2% HR-7 and 1/2 #sk gas check. Full returns.

5 1/2" 17.93" Liner Liner top at 11,368'. Set at 13,426' w/260 sx Class "H" cement.

PBTD

ATTACHMENT TO FORM 3160-4

FEBRUARY 11, 1988