

OIL CONSERVATION DIVISION
P. O. BOX 2086
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
N/A	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - "A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Marshall & Winston, Inc.		8. Farm or Lease Name McNeill "A"
3. Address of Operator 310 West Tower, #10 Desta Drive, Midland, TX 79705		9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> <u>3000</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>West</u> LINE, SECTION <u>6</u> TOWNSHIP <u>21S</u> RANGE <u>38E</u> NMPM.		10. Field and Pool, or Wildcat Wantz - Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3556.7' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUS AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUS AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1/6/88 Drilled 12-1/4" hole to 1602'. Cemented 8-5/8", 23# surface casing w/ 700 sxs. Class "C" + 6% gel + 2% CaCl followed by 200 sxs. Class "C" + 2% CaCl. Bumped plug w/ 1000#. Held OK. Circ. 100 sxs. cement to pit. Tested casing to 1000# for 30 minutes, OK.

1-19-88 Drilled 7-7/8" hole to 7815'. Ran 5-1/2", 17# & 15.5# production casing to TD. Placed DV tool @ 5478'. Cemented 1st stage w/ 560 sxs. Class "H" + 5# salt + .8% Halad 322 and 210 sxs Class "H" + 10# Micro-bond + .5% Halad 322. Bumped plug w/ 1700#. Cemented 2nd stage w/ 1625 sxs. Lite + 100 sxs. Class "H". Circ 20 sxs. cement to pit. Drilled out DV tool & tested casing to 1000#, OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul Kautz TITLE Engineer DATE March 8, 1988

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE MAR 11 1988

CONDITIONS OF APPROVAL, IF ANY:

APR 10 1968
FBI - NEW YORK