

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
BY	
TO	
FROM	
OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p>5a. Indicate Type of Lease</p> <p>State <input checked="" type="checkbox"/> Fee <input type="checkbox"/></p>	
<p>5. State Oil & Gas Lease No.</p>	
<p>7. Unit Agreement Name</p>	
<p>8. Farm or Lease Name</p> <p>State "A"</p>	
<p>9. Well No.</p> <p>1</p>	
<p>10. Field and Pool, or Wildcat</p> <p>Eumont Yates 7-Rvrs-Q</p>	
<p>12. County</p> <p>Lea</p>	

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
John H. Hendrix Corporation

Address of Operator
223 W. Wall, Suite 525, Midland, TX 79701

Location of Well
UNIT LETTER 0, 735 FEET FROM THE South LINE AND 1929 FEET FROM East LINE, SECTION 30 TOWNSHIP 20S RANGE 37E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3531' G.L.

<p>Check Appropriate Box To Indicate Nature of Notice, Report or Other Data</p>	
<p>NOTICE OF INTENTION TO:</p> <p>FORM REMEDIAL WORK <input type="checkbox"/></p> <p>PROBABLY ABANDON <input type="checkbox"/></p> <p>PLUG OR ALTER CASING <input type="checkbox"/></p> <p>OTHER <input type="checkbox"/></p>	<p>SUBSEQUENT REPORT OF:</p> <p>PLUG AND ABANDON <input type="checkbox"/></p> <p>REMEDIAL WORK <input type="checkbox"/></p> <p>COMMENCE DRILLING OPNS. <input type="checkbox"/></p> <p>CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/></p> <p>OTHER <input type="checkbox"/></p> <p>Casing Record <input type="checkbox"/></p>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 6-2-88 - Spudded well.
- 6-3-88 - Ran 26 jts. 8-5/8" O.D. 24#, K-55 ST&C csg. set at 1076'. Cemented w/ 350 sx. Class "C" + 4% gel, 1/4# Flocele, 2% CaCl, tailed in w/ 200 sx. Class "C" containing 2% CaCl. Plug down at 5:30 P.M., 6-3-88. Cement circulated.
- 6-4-88 - Tested 8-5/8" csg. & BOP to 1000 psi - OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ronnie H. Westbrook TITLE Vice-President DATE August 2, 1988

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT 1 SUPERVISOR DATE 468

CONDITIONS OF APPROVAL, IF ANY: