

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	LG-7267

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator BTA OIL PRODUCERS	8. Farm or Lease Name Chiso -D-, 8711 JV-P
3. Address of Operator 104 South Pecos, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER -K- 1980 FEET FROM THE South LINE AND 2310 FEET FROM THE West LINE, SECTION 23 TOWNSHIP 22-S RANGE 34-E NMPM.	10. Field and Pool, or Wildcat Ojo Chiso (Morrow)
15. Elevation (Show whether DF, RT, GR, etc.) 3447' GR 3467' RKB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-30-88 Depth 11,200' Cmt'd 7 5/8" 39# P110 LTC csg @ 11,200' w/ 2200 sx.
PD: 1:45 A.M. 10-31-88

10-31-88 Circ "DV" tool @ 5998' & WOC 10 hrs between stages. Cmt Circ.
Set slips & cut off csg. Install spool & BOP's. Tested "DV" tool
& float collar to 2500 psi w/ 9.0 ppg brine. Drlg "DV" tool
@ 5998'.

11- 1-88 Depth 11,300' Drlg 6 1/2" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dorothy Voughton TITLE Regulatory Supervisor

DATE 11/2/88

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: