Navember 1983) Formerly 9-331)	UNITED STATES DEPARTME. OF THE INTERI	•••	
SUN (Do not use this	BUREAU OF LAND MANABLEMENT OF LOND REPORTS OF COUNTY OF THE PROPERTY OF SUCH PROPERTY OF SUCH PROPERTY.	NOWELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS WELL	OTHER	און ב און ב און	7. UNIT AGREEMENT NAME NMF/
2. NAME OF OPERATOR 3. ADDRESS OF OPERATOR	Inc.	C. ARE	8. FARM OR LEASE NAME Britt B 9. WELL NO.
4. LOCATION OF WELL (I See also space 17 bel At surface	Report location clearly and in accordance with any ow.) Unit Letter	88240 State requirements.*	10. FIELD AND POOL, OR WILDCAT
J	130' FNL + 1900' F	WL	11. SEC., T, E., M., OR BLE. AND SURVEY OR AREA
30-025-	3047 3551' G/	RT, GR, etc.)	Sec. 15, T205, R37F 12. COUNTY OR PARISH 13. STATE
16.	Check Appropriate Box To Indicate N	ature of Notice. Report or C	Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	MULTIPLE COMPLETE ABANDON* CHANGE PLANS	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (NOTE: Report results Completion or Recognile	ALTERING WELL ALTERING CASING ABANDONMENT* of multiple completion on Well tion Report and Log form.)
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			
We propose to complete the Skaggs Alo gas zone as the top side of a Cass Penn/Skaggs Alo Dual Completion.			
top side of a Cass Henn/ 5 Kaggs Also Dual Completion. Kill well with 9 ppg brine. Poot w/production equipment,			
set CIBP @ 7630' (top Cass Penn perss @ 7653'). Selectively perforate, acid frac and swab test Skaggs Abo in			
3 stages. Retrieve CIBP and RIH with Dual Production			
Equip. Place well on production. Estimated starting			
date for	- this procedure is	July 1, 1989	,
,	he foregoing is true and correct		
SIGNED WUSSE	·		DATE 6/6/89
(This space for Federa	or State office need R. GLASS CHIEF	, NUNTERAL FILMATA CES	
APPROVED BYCONDITIONS OF APP			DATE 6-15-89

*See Instructions on Reverse Side