

6. RU WEDGE WL. PERF ATOKA W/ 3 1/8" CSG GUN 13 GM CHARGES .38" HOLE. CORRELATE W/ ATTACHED SCHLUMBERGER GR-CBL DATED 10/20/89. AS FOLLOWS:

ATOKA (12080-12092)	12'	4 SPF	48 HOLES
(12142-12148)	6'	4 SPF	24 HOLES
(12204-12214)	10'	4 SPF	40 HOLES
(12224-12236)	12'	4 SPF	48 HOLES
(12240-12244)	4'	4 SPF	16 HOLES
(12248-12252)	4'	4 SPF	16 HOLES
(12270-12276)	6'	4 SPF	24 HOLES
(12284-12290)	6'	4 SPF	24 HOLES

TOTALS	60'	4SPF	240 HOLES
--------	-----	------	-----------

7. RIH W/ PN & 4 1/2" UNI PKR VI ON/OFF TOOL ON 24 JTS (740') 2-3/8" 4.7# N-80 TBG + 2-7/8" 6.5# N-80 TGB (11290'). SET PKR @ $\pm$ 12030' TO ISOLATE THE ATOKA (12080-12290).
8. RU HOWCO. ACDZ ATOKA (12080-12290) DWN 2-7/8" X 2-3/8" TAPER @ 6 BPM. EXP TP = 3500 PSI. MAX TP = 5000 PSI AS FOLLOWS:
- A) 200 GALS 15% NE FE HCL
 - B) 3000 GALS 75% FOAMED 15% NE FE HCL
 - C) 2000 GALS 75% FOAMED 15% NE FE HCL 1 #/GAL TBA - 110
 - D) 3000 GALS 75% FOAMED 15% NE FE HCL
 - E) FLUSH W/ $\pm$ 50,000 SCF N₂
9. OPEN WELL AND FLOW BACK IMMEDIATELY.
10. FLOW TO TEST. REPORT TO DALLAS.
11. ND BOP. NU WELLHEAD.
12. RR.