

COMPLETIONS SEC 26 TWP 22S RGE 34E
PI# 30-T-0033 05/11/90 30-025-30699-0000 PAGE 3

ORYX ENERGY
2

OJO CHISO FEDERAL

D DG

PRODUCTION TEST DATA

TP 1500
NATURAL

LOGS AND SURVEYS /INTERVAL,TYPE/

LOGS11530-13595	CBL	11700-12497	DI	11700-12497	GR
LOGS12497-13650	DI	12497-13650	GR	11700-12497	SDBL
LOGS11700-12497	DSN	11700-12497	GR	11700-12497	CALP
LOGS12497-13650	SDBL	12497-13650	DSN	12497-13650	GR
LOGS12497-13650	CALP	12408-12408	RFT	13503-13503	RFT

DRLG SHOWS OR POROSITY ZONES /INTERVAL,FORMATION,DESC

12150-12174	ATOKA	GAS	12400-12407	ATOKA	GAS
-------------	-------	-----	-------------	-------	-----

DRILLING BREAKS

12150-12174	(ATOKA)	SML SHW GAS	S
12400-12407	(ATOKA)	SHW GAS	S
12908-12912	(MORROW)	NS	
12931-12936	(MORROW)	NS	
12944-12952	(MORROW)	NS	
13086-13090	(MORROW)	NS	
13252-13256	(MORROW)	NS	
13288-13292	(MORROW)	NS	

DRILLING PROGRESS DETAILS

	ORYX ENERGY
	BOX 1861
	MIDLAND, TX 79702
	915-688-0300
10/05	LOC/1989/
12/12	DRLG 1170
12/13	DRLG, NO DETAILS
12/19	DRLG 4138
12/27	DRLG 7580
01/02	DRLG 9806
01/05	DRLG 10670
01/12	11835 TD, FSG
01/16	DRLG 11846
01/23	12434 TD, CIRC

CONTINUED

COMPLETIONS SEC 26 TWP 22S RGE 34E
PI# 30-T-0033 05/11/90 30-025-30699-0000 PAGE 4

ORYX ENERGY
2

OJO CHISO FEDERAL

D DG

DRILLING PROGRESS DETAILS

01/30 DRLG 12781
02/07 DRLG 13447
02/12 13650 TD, CIRC
02/12 DEVIATION SURVEYS @ 505 (1/4 DEG), 1004 (1/4 DEG), 1253 (3/4 DEG), 1800 (3/4 DEG), 2079 (1 DEG), 2580 (1 1/2 DEG), 2968 (1 1/4 DEG), 3289 (1 3/4 DEG), 3678 (2 3/4 DEG), 3907 (2 1/4 DEG), 4070 (1 1/4 DEG), 4185 (1 DEG), 4850 (1/4 DEG), 5335 (1 3/4 DEG), 5693 (1 1/2 DEG), 5988 (3/4 DEG), 6380 (1 1/2 DEG), 6732 (1 1/2 DEG), 7092 (1 1/2 DEG), 7443 (1 1/2 DEG), 7942 (1 1/2 DEG), 8590 (1 1/2 DEG), 8945 (3 DEG), 9120 (4 1/2 DEG), 9182 (4 1/4 DEG), 9225 (4 DEG), 9400 (4 1/4 DEG), 9445 (4 3/4 DEG), 9506 (3 3/4 DEG), 9587 (3 3/4 DEG), 9662 (3 3/4 DEG), 9756 (3 1/2 DEG), 9867 (3 1/4 DEG), 9943 (2 3/4 DEG), 10066 (2 DEG), 10282 (2 DEG), 10487 (2 1/4 DEG), 10806 (1 DEG), 11132 (2 1/4 DEG), 11423 (2 1/2 DEG), 12000 (1 1/2 DEG), 12520 (2 DEG), 12830 (1 1/4 DEG), 13120 (1 1/4 DEG), 13625 (2 DEG)
02/21 13650 TD, WOCT
03/20 13650 TD, PE 13382, TSTG
04/02 13650 TD, PE 13382, SI
04/10 13650 TD, PE 12350, SI BHP
04/18 13650 TD, PE 12350, WOPT
05/10 LOCAL CALL: ATOKA BANK 12140
10-15 FT FLARE @ 12434
4-5 FT FLARE @ 12522-12534
4-6 FT FLARE @ 12615-12715
35-40 FT FLARE @ 12844 & 13144
3-5 FT FLARE @ 13595
30-40 FT FLARE @ TD
RAN RFT @ 12408 1/2, REC 54.5 CFT GAS, 2400 CC
FILT, 9368 PSI (ATOKA SD)
RAN RFT @ 13503, 7736 PSI (MORROW)
05/10 POROUS ZONES:
ATOKA LM 12140-12394, GAS
ATOKA SD 12404-12410, GAS
MORROW SD 13448-13474, GAS
MORROW SD 13498-13510, GAS
TD REACHED 02/08/90 RIG REL 02/14/90

CONTINUED

COMPLETIONS
PI# 30-T-0033 05/11/90 SEC 26 TWP 22S RGE 34E
30-025-30699-0000 PAGE 5

ORYX ENERGY
2

OJO CHISO FEDERAL

D DG

DRILLING PROGRESS DETAILS

05/10 13650 TD, PB 12350
COMP 2/12/90, IPCAOF 1799 MCFGPD, GOR 7438
GTY 48.2, GTY (GAS) .683,
SIWHP 5020, SIBHP 6509
PROD ZONE - ATOKA 12156-12316
NO CORES OR DSTS, 22 SDWL CORES RPTD