

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
NOV 22 2 12 PM '91

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a disused well.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

BTA Oil Producers

3. Address and Telephone No.

104 S. Pecos, Midland, TX 79701

915-682-3753

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL & 990' FWL
Sec 26, T22S, R34E

Unit M

SW/SW

5. Lease Designation and Serial No.
NM43564

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

#3, Ojo Chiso Fed, 8817 JV-F

9. API Well No.

30-025-30733

10. Field and Pool, or Exploratory Area

Antelope Ridge Morrow

11. County or Parish, State

Lea County, N.M.

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other CSG
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(No e. Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-27-91 Depth 5224', Cmtd 9-5/8" S95 & K55 40# LTC csg @ 5224' w/2500 sx, Cmt circ, WOC, Set slips & cut off, Installed spool & BOP's, Cld out to shoe, Tstd csg to 2000 psi, WOC 18 hrs total, Drld shoe, Drlg 8-3/4" hole.

11-19-91 Depth 11,814', Cmtd 7" 29# S95 LTC csg @ 11814' w/2100 sx, Circ DV tool @ 6485, Cmt circ, WOC, Set slips & cut off csg, Installed csg spool & BOP's.

11-20-91 Tstd DV tool & float collar to 2500 psi W/10 ppg brine wtr.

11-21-91 Drlg DV tool @ 6485', Drlg 6-1/8" hole.

RECEIVED
NOV 22 10 33 AM '91

14. I hereby certify that the foregoing is true and correct.

Signed

Carolyn Day

Title Regulatory Administrator

Date 11-21-91

(This space for Federal or State office use.)

Approved by

Conditions of approval, if any:

Title

Date