Submit to Appropriate
District Office
State Lease – 6 copies
Fee Lease – 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO. 30-025-31144

5. Indicate Type of Lease STATE [X] FEE [ ]

6. State Oil & Gas Lease No. A-2614

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL [X] GAS WELL [ ] DRY [ ] OTHER

b. Type of Completion: NEW WELL [X] WORK OVER [ ] DEEPEN [ ] PLUG BACK [ ] DIFF RESVR [ ] OTHER

7. Lease Name or Unit Agreement Name: McDonald St. A/C "1"

2. Name of Operator: Marathon Oil Company

8. Well No. 45

3. Address of Operator: P.O. Box 552, Midland, TX 79702

9. Pool name or Wildcat: S. Eunice (Seven Rivers Queen)

4. Well Location
Unit Letter A : 660 Feet From The North Line and 510 Feet From The East Line

Section 16 Township 22-S Range 36-E NMPM Lea County

10. Date Spudded	11. Date T.D. Reached	12. Date Compl. (Ready to Prod.)	13. Elevations (DF & RKB, RT, GR, etc.)	14. Elev. Casinghead
4/30/91	5/7/91	9/19/91	3355' GR	3355' GR

15. Total Depth	16. Plug Back T.D.	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools	Cable Tools
4000'	3970'			All	

19. Producing Interval(s), of this completion - Top, Bottom, Name: 3732'-3912' Seven Rivers Queen

20. Was Directional Survey Made: Yes

21. Type Electric and Other Logs Run: LDT/CNL/GR/CAL, GR/CCL/CBL

22. Was Well Cored: No

23. **CASING RECORD** (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	449'	11"	350sx Class"C"+2% CaCl	
				circ'd 78sx	
5 1/2"	15.5#	4000'	7 7/8"	750sx65:35:4 poz+3#/sx salt+1/4#/sx	
				celloflake+466sx Class "C"+3% KCl,	
				circ'd 170sx	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8"	3696'	

26. Perforation record (interval, size, and number)
3732'-3838', .4" shot, 126 holes
3812'-3912', .4" shot, 124 holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
3812'-3912'	Frac w/66000# 20/40 Brady sand+12000# 20/40 resin coated sand+20000gal cross-linked gel

PRODUCTION

28.

Date First Production	Production Method (Flowing, gas lift, pumping - Size and type pump)	Well Status (Prod. or Shut-in)
9/19/91	2 1/2" x 1 3/4" x 16' x 17' x 18' RHBC Rod Pump	Producing

Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
9/24/91	24			8	20	92	2500

Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)
	50		8	20	92	-

29. Disposition of Gas (Sold, used for fuel, vented, etc.): Vented

Test Witnessed By: Tony Hallum

30. List Attachments

31. *I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief*

Signature Carl A. Bagwell Printed Name Carl A. Bagwell Title Eng. Techn. Date 10/18/91

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen 3812'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3960'	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permain	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....

No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
3812'	3960'	148'	Queen (Dolo)				
3960'	3999'	39'	Grayburg (Dolo)				

RECEIVED

NOV 05 1991

OCD

HOBBS OFFICE