## Submit 3 Copies to Appropriate District Office

APPROVED BY --

CONDITIONS OF APPROVAL, IF ANY:

## State of New Mexico Energy, Minerais and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I

OIL CONSERVATION DIVISION

WELL API NO.

DISTRICT II Santa Fe, New Mexico 87504-2088	30-025-31160	
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lesse STATE X FEE	
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410	6. State Oil & Gas Lease No.	
THE PERCETS ON WELLS		
SUNDRY NOTICES AND REPORTS ON WELLS  ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name	
I. Type of Well:	McDonald State A/C l	
2. Name of Operator	8. Well No. 34	
Marathon Oil Company		
3. Address of Operator P. O. Box 552, Midland, TX 79702	9. Pool same or Wildest South Eunice SK-GIN	
P. O. Box 552, Mildrand, The 79752  4. Well Location  Unit Letter H: 2620 Feet From The north Line and 25	Feet From The east Line	
20 A R 36-F	NMPM Lea County	
Section 16 Township 22-S Range 30-E 10. Elevation (Show weather DF, RKB, RT, GR, etc.)		
///////	Owner or Other Data	
Check Appropriate Box to Indicate Nature of Notice, I	Report, of Other Data  BSEQUENT REPORT OF:	
NOTICE OF INTENTION TO:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING	
PERPORM REMEDIAL WOLLD	NG OPNS. PLUG AND ABANDONMENT	
TEMPOHAHILY ABANDON CASING TEST AND	CEMENT JOB X	
PULL OR ALTER CASING		
OTHER:		
OTHER: OTHER:	Julius estimated date of starting any propessed	
	cluding estimated date of starting any proposed	
12. Describe Proposed or Completed Operations (Clearly state all persinent details, and give persinent dates, inc. work) SEE RULE 1103.  MIRU Cactus #54. Spud 11" hole @ 1045 hrs 7-28-91. Drld to 450'. Ran 11 jts 8-5/8", 406'. Mixed & pumped 350 sx Class "C" + 1% CaCl <sub>2</sub> . Circ'd 115 sx to surface. CIP @ 1 3M csg head. Tested weld to 500 psi. N/U 11" 3M dual ram & annular BOP. Tested rams & floor valves 300/3000 psi. TIH to 406'. Total WOC time - 18 hrs. Test csg to 1000	24#, K-55, 8 RD csg to 450'. Insert float @ 700 hrs 7-28-91. Cut csg & weld on 8-5/8" 11" 300/3000 psi, annular & mud lines to 1500 psi	
OTHER:	24#, K-55, 8 RD csg to 450'. Insert float a 700 hrs 7-28-91. Cut csg & weld on 8-5/8" 11" 300/3000 psi, annular & mud lines to 1500 psi psi. Drld cmt to 426', test csg to 1000 psi. Changed rams to 5-1/2" & tested door seals to xed & pumped 988 sx, 35/65 Class "C" poz mix +	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, incompart) SEE RULE 1103.  AIRU Cactus #54. Spud 11" hole @ 1045 hrs 7-28-91. Drld to 450'. Ran 11 jts 8-5/8", 406'. Mixed & pumped 350 sx Class "C" + 1% CaCl <sub>2</sub> . Circ'd 115 sx to surface. CIP @ 1 8M csg head. Tested weld to 500 psi. N/U 11" 3M dual ram & annular BOP. Tested rams & floor valves 300/3000 psi. TIH to 406'. Total WOC time - 18 hrs. Test csg to 1000 Resumed drlg w/ 7-7/8" bit.  Orld to 4000'. R/U WL lubricator & test to 350 psi. Ran CNL/LDT/CAL 3992'-surface.  1500 psi. Ran 97 jts 5-1/2", 15.5#, K-55, LTC csg to 4000', float collar @ 3858'. Mi	24#, K-55, 8 RD csg to 450'. Insert float a 700 hrs 7-28-91. Cut csg & weld on 8-5/8" 11" 300/3000 psi, annular & mud lines to 1500 psi psi. Drld cmt to 426', test csg to 1000 psi. Changed rams to 5-1/2" & tested door seals to xed & pumped 988 sx, 35/65 Class "C" poz mix +	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, incomplete SEE RULE 1103.  ATRU Cactus #54. Spud 11" hole a 1045 hrs 7-28-91. Drld to 450'. Ran 11 jts 8-5/8", 106'. Mixed & pumped 350 sx Class "C" + 1% Caclo. Circ'd 115 sx to surface. CIP a 1 state of the state of the surface of the surfa	24#, K-55, 8 RD csg to 450'. Insert float a 700 hrs 7-28-91. Cut csg & weld on 8-5/8" 11" 300/3000 psi, annular & mud lines to 1500 psi psi. Drld cmt to 426', test csg to 1000 psi. Changed rams to 5-1/2" & tested door seals to xed & pumped 988 sx, 35/65 Class "C" poz mix + te. CIP a 0525 hrs 8-03-91. N/D BOP's,	
12. Describe Proposed or Completed Operations (Clearly state all persisens details, and give persisens dates, incompart) SEE RULE 1103.  MIRU Cactus #54. Spud 11" hole @ 1045 hrs 7-28-91. Drld to 450'. Ran 11 jts 8-5/8", 106'. Mixed & pumped 350 sx Class "C" + 1% CaCl <sub>2</sub> . Circ'd 115 sx to surface. CIP @ 1 lim csg head. Tested weld to 500 psi. N/U 11" 3M dual ram & annular BOP. Tested rams of floor valves 300/3000 psi. TIH to 406'. Total WOC time - 18 hrs. Test csg to 1000 lessumed drlg w/ 7-7/8" bit.  Orld to 4000'. R/U WL lubricator & test to 350 psi. Ran CNL/LDT/CAL 3992'-surface. 1500 psi. Ran 97 jts 5-1/2", 15.5#, K-55, LTC csg to 4000', float collar @ 3858'. Mi lim collar lim w/ 591 sx Class "C" + 3% KCl. Circ'd 21 sx to surface installed 11" 3M x 7-1/16" 3M tbg head. Rig released @ 0730 hrs 8-03-91.	24#, K-55, 8 RD csg to 450'. Insert float a 700 hrs 7-28-91. Cut csg & weld on 8-5/8" 11" 300/3000 psi, annular & mud lines to 1500 psi psi. Drld cmt to 426', test csg to 1000 psi. Changed rams to 5-1/2" & tested door seals to xed & pumped 988 sx, 35/65 Class "C" poz mix + e. CIP a 0525 hrs 8-03-91. N/D BOP's,	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, incomplete Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, incomplete SEE RULE 1103.  ATRU Cactus #54. Spud 11" hole a 1045 hrs 7-28-91. Drild to 450'. Ran 11 jts 8-5/8", 106'. Mixed & pumped 350 sx Class "C" + 1% Cacl Circ'd 115 sx to surface. CIP a 1 sh cash can be seen a surface of the surfa	24#, K-55, 8 RD csg to 450'. Insert float a 700 hrs 7-28-91. Cut csg & weld on 8-5/8" 11" 300/3000 psi, annular & mud lines to 1500 psi psi. Drld cmt to 426', test csg to 1000 psi. Changed rams to 5-1/2" & tested door seals to xed & pumped 988 sx, 35/65 Class "C" poz mix + te. CIP a 0525 hrs 8-03-91. N/D BOP's,	
12. Describe Proposed or Completed Operations (Clearly state all persinent details, and give persinent dates, inc. work) SEE RULE 1103.  ALRU Cactus #54. Spud 11" hole a 1045 hrs 7-28-91. Drld to 450'. Ran 11 jts 8-5/8", 106'. Mixed & pumped 350 sx Class "C" + 1% CaCl2. Circ'd 115 sx to surface. CIP a 1 st convolves 300/3000 psi. TIH to 406'. Total WOC time - 18 hrs. Test csg to 1000 resumed drlg w/ 7-7/8" bit.  Alruction of the following the first the state of the first test of 350 psi. Ran CNL/LDT/CAL 3992'-surface.  Alruction of the first test of the first test of 350 psi. Ran CNL/LDT/CAL 3992'-surface.  Alruction of the first test of the first test of 350 psi. Ran CNL/LDT/CAL 3992'-surface.  Alruction of the first test of the first test of test	24#, K-55, 8 RD csg to 450'. Insert float a 700 hrs 7-28-91. Cut csg & weld on 8-5/8" 11" 300/3000 psi, annular & mud lines to 1500 psi psi. Drld cmt to 426', test csg to 1000 psi. Changed rams to 5-1/2" & tested door seals to xed & pumped 988 sx, 35/65 Class "C" poz mix + e. CIP a 0525 hrs 8-03-91. N/D BOP's,	