

- 9/21/91 - POOH w/tbg & bit. Test blind rams to 1000 psig. RU Wedge. Ran GR-CCL-CBL from 3919'-3506' w/0 psig on csg. Relogged from 3919' to 40' w/1000 psig on csg. RU & test full lubricator to 1000 psig. RIH w/4" perf gun. Perforated 3661'-65', 3680'-3708', 3715'-17', 3724'-33' & 3738'-55' w/4 JSPF (245 holes). On 3rd run gun stuck while pulling out of hole @ 3250'. Pulled out of rope socket. RIH w/4 11/16" overshot w/3 1/8" grapple & 3 1/2" bumper sub on 2 7/8" tbg. Tagged fish @ 3902'. Latched onto fish & POOH w/tools & perf gun. Made last two runs to finished perforating. RD Wedge. RIH w/50 jts 2 7/8" killstring. SDFN.
- 9/22/91 - SDFWE.
- 9/23/91 - SDFWE.
- 9/24/91 - POOH w/killstring. RIH w/5 1/2" Halliburton RTTS pkr on 2 7/8" J-55 tbg. Set pkr @ 3572'. Dropped SV & test tbg to 4000 psig. Fished SV. RU BJ & test lines to 4000 psig. Pressure backside to 500 psig. Breakdown perfs 3661'-3755' @ 2400 psig. Acidized perfs w/5500 gals 15% NEFE HCl & 1200# rock salt. Saw slight diversion. Max - 2800 psig. Avg - 1500 psig @ 5.6 bpm. ISIP - Vac. RD BJ. RIH w/swab. FL - 2300' FS. Made 5 swab runs & recov'd 14 BW. Swabbed well dry. SOH w/tbg & pkr. SDFN.
- 9/25/91 - FOOH w/2 7/8" J-55 tbg & pkr. RIH w/5 1/2" Baker AD-1 nickel coated tension pkr on 2 3/8" Duoline tbg. ND BOP & NU tree. Displace annulus w/pkr fluid & set pkr @ 3608'. Pressure backside to 500 psig. Bleed off pressure. RD PU. Dropped from report waiting on injection facilities.

FINAL REPORT.