

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FWL, Sec. 6-T22S-R32E, NMPM

5. Lease Designation and Serial No.

NM 64605

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Rosemary AJB Federal

9. API Well No.

30-025-31227

10. Field and Pool, or Exploratory Area

Und. Livingston Ridge Delawar

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Intermediate Casing

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-6-91. Ran 109 joints 8-5/8" 32# HC-80 and J-55 ST&C casing as follows: 13 jts 32# HC-80 and 96 jts 32# J-55 casing set 4539'. Guide shoe set 4539', float collar set 4492'. Cemented w/1400 sx Pacesetter Lite "C" with 1/4# Flocele + 10# salt (yield 1.94, wt 12.9). Tailed in w/200 sx "C" + 1% CaCl2 (yield 1.32, wt 14.8). PD 10:15 PM 5-6-91. Bumped plug to 2500 psi, float held OK. Circulated 150 sacks. WOC. Drilled out 2:00 PM 5-8-91. WOC 38 hrs and 45 minutes. Reduced hole to 7-7/8" and resumed drilling.

FILED FOR RECORD

JUN 7 1991

CLOSBAD, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

[Signature]

Title Production Supervisor

Date 5-23-91

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any:

RECEIVED

JUN 20 1991

GO
HOBBS OFFICE