

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
P.O. Box 1980
Hobbs, NM 88241
FORM APPROVED
Bureau of Land Management, 1004-0135

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPlicate

1. Type of well
☐ Oil ☐ Gas ☒ Other WATER SUPPLY

2. Name of Operator
CHEVRON U.S.A. INC.

3. Address and Telephone No.
P. O. Box 1150, Midland, TX 79702 (915)687-7148

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
2540' FNL & 1220' FWL UNIT H
SEC 1, T22S, R36E

5. Lease Designation and Serial No.
NM 62665

6. If Indian, Allottee or Tribe Name
N/A

7. If Unit or CA, Agreement Designation
ARROWHEAD GRAYBURG UNIT

8. Well Name and No.
601

9. API Well No.
30-025-31303

10. Field and Pool, or Exploratory Area
SAN ANDRES WATER SUPPLY

11. County or Parish, State
LEA, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

12 TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimate date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

ATTEMPTED TO WORK PAST 1942' WITH NO SUCCESS. MILLED TO 2000'; TAGGED SOLID @ 1941'. ROTATED 1900'-1935', TRIED TO FIND CSG TOP WITH NO SUCCESS. ATTEMPTED TO CUT WINDOW IN PARTED CSG @ 1928' WITH NO SUCCESS. RECEIVED PERMISSION FROM VINCE W/BLM TO PLUG AS FOLLOWS: PUMPED 440 SX CL "C" @1781', TAIL W/440 SX CL "C". PRESS 1600# TO RVRS OUT, NO SUCCESS. CIRC 45 SX TO PIT. SQZD 836 SX IN FORM. PRESS SQZ 1000PSI. SPOTTED 50' CMT PLUG ON TOP OF CIRC SET @ 1781'. PERFD 4 SQZ HOLES @ 1223'. SET CIRC @ 1150', UNABLE TO PUMP THRU CIRC. PERFD 4 SQZ HOLES @ 1140', UNABLE TO PUMP INTO PERFS. SPOTTED 25 SACK CMT PLUG ON TOP OF CIRC @ 1150' (1140'-1040'). SPOTTED 90 SACK BALANCED PLUG 350' - SURF. FINISHED FILLING WELL UP W/CMT.

WELL P&A'D 2/27/97.

Approved as to planning of the well bore
Location and depth of plug back until
surface plug is in place and cemented.

14. I hereby certify that the foregoing is true and correct

Signed G. K. Relyea Title T. A.

Date 5/12/97

(This space for Federal or State office use)

Approved by (ORIG. SGD.) ALEXIS C. SWOBODA Title PETROLEUM ENGINEER

Date MAY 14 1997

Conditions of approval, if any: