

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-025-31576

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.
VB 134

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Kiwi AKX State

1. Type of Well:
OIL WELL GAS WELL OTHER

8. Well No.
1

2. Name of Operator
YATES PETROLEUM CORPORATION

9. Pool name or Wildcat
East Livingston Ridge Delaware

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter P : 330 Feet From The South Line and 330 Feet From The East Line
Section 16 Township 22S Range 32E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3704' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

| | | | |
|--|---|--|---|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | | CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> | |
| OTHER: _____ <input type="checkbox"/> | | OTHER: _____ <input type="checkbox"/> | |

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" conductor hole 1:00 PM 4-28-92. Set 40' of 20" conductor. Resumed drilling 17-1/2" hole 2:00 PM 4-30-92. TD'd 17 1/2" hole 2:00 PM 4-30-92. Ran 20 joints 13-3/8" 54.5# J-55 casing set 871', Guide shoe set 871', insert float set 826'. Cemented w/600 sx PSL with 2% CaCl2 (yield 1.76, wt 12.9). Tailed in w/250 sx "C" with 2% CaCl2 (yield 1.33, wt 14.8). PD 2:45 PM 5-1-92. Bumped plug to 600 psi, float held OK. Circulated 140 sacks cement. WOC. Drilled out 4:45 AM 5-2-92. WOC 14 hours. Reduced hole to 11" and resumed drilling.

Notified Joan, NMOCD, Hobbs, NM - did not witness.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 5-6-92
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
MAY 07 1992
OCD HOBBS OFFICE