

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO.
30-025-31600

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
VB-134

7. Lease Name or Unit Agreement Name

Kiwi AKX State

8. Well No.

4

9. Pool name or Wildcat

E. Livingston Ridge-Delaware

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____

b. Type of Completion:
NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OTHER _____

2. Name of Operator
YATES PETROLEUM CORPORATION (505) 748-1471

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter 0 : 330 Feet From The South Line and 1650 Feet From The East Line
Section 16 Township 22S Range 32E NMPM Lea County

10. Date Spudded 6-9-92 11. Date T.D. Reached 6-25-92 12. Date Compl. (Ready to Prod.) 7-11-92 13. Elevations (DF & RKB, RT, GR, etc.) 3705' GR 14. Elev. Casinghead

15. Total Depth 8760' 16. Plug Back T.D. 8690' 17. If Multiple Compl. How Many Zones? 18. Intervals Drilled By Rotary Tools 0-8760' Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name 7266-8638' Delaware 20. Was Directional Survey Made No

21. Type Electric and Other Logs Run CNL/LDT; DLL 22. Was Well Cored No

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
20"		55'	26"	Redi-Mix	
13-3/8"	54.5#	867'	17 1/2"	750 sx	
8-5/8"	32#	4540'	11"	1600 sx	
5-1/2"	15.5 & 17#	8760'	7-7/8"	938 sx	

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8"	7000'	

26. Perforation record (interval, size, and number)

7266-8638' w/130 - .42" Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
7266-8638'	w/3250g. 7 1/2% NEFE. SF w/5200g
	35# linear gel + 28350g. 35#
	XL gel+72000# 20/40 sand.

PRODUCTION

28. Date First Production 7-6-92		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping					Well Status (Prod. or Shut-in) Producing	
Date of Test 7-11-92	Hours Tested 24	Choke Size 2"	Prod'n For Test Period	Oil - Bbl. 196	Gas - MCF 269	Water - Bbl. 274	Gas - Oil Ratio 1372	
Flow Tubing Press. 60	Casing Pressure 60	Calculated 24- Hour Rate	Oil - Bbl. 196	Gas - MCF 269	Water - Bbl. 274	Oil Gravity - API - (Corr.) 42°		

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold - Connected to Yates Gas Gathering 7-6-92

Test Witnessed By
Ed Perry

30. List Attachments

Deviation Survey, Logs

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Juanita Goodlett Printed Name Juanita Goodlett Title Production Supv. Date 7-14-92

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy Rustler 897
T. Salt
B. Salt 4442
T. Yates
T. 7 Rivers
T. Queen
T. Grayburg
T. San Andres
T. Glorieta
T. Paddock
T. Blinbry
T. Tubb
T. Drinkard
T. Abo
T. Wolfcamp
T. Penn
T. Cisco (Bough C)

T. Bell-
T. Canyon 4751
T. Strawn
T. Atoka
T. Miss
T. Devonian
T. Silurian
T. Montoya
T. Simpson
T. McKee
T. Ellenburger
T. Gr. Wash
T. Delaware Sand
T. Bone Springs 8653
T. Cherry Canyon-5804
T. Brushy Canyon-7444
T.
T.

Northwestern New Mexico

T. Ojo Alamo
T. Kirtland-Fruitland
T. Pictured Cliffs
T. Cliff House
T. Menefee
T. Point Lookout
T. Mancos
T. Gallup
Base Greenhorn
T. Dakota
T. Morrison
T. Todilto
T. Entrada
T. Wingate
T. Chinle
T. Permian
T. Penn "A"

T. Penn. "B"
T. Penn. "C"
T. Penn. "D"
T. Leadville
T. Madison
T. Elbert
T. McCracken
T. Ignacio Otzte
T. Granite
T.
T.
T.
T.
T.
T.
T.
T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	55	55	Surface				
55	867	812	Redbeds				
867	3800	2933	Salt, Anhy				
3800	3828	28	Salt				
3828	3980	152	Anhy				
3980	4440	460	Salt				
4440	4750	310	Anhy				
4750	4830	80	LS, Sh				
4830	4976	146	SS, LS				
4976	5580	604	SS, Sh				
5580	5694	114	SS, Sh, LS				
5694	6010	316	SS, LS				
6010	7690	1680	SS, Sh				
7690	7980	290	SS				
7980	8760	780	SS, Sh, LS				