

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR NUMBER
OF COPIES REQUIRED
(Other instructions on re-
verse side)

Modified Form No.
ND60-3160-4
LEASE DESIGNATION AND SERIAL NO.
NM-27805

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Paisano Federal

9. WELL NO.

#3

10. FIELD AND POOL, OR WILDCAT

Livingston Ridge Delaware East

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 15-22S-32E

12. COUNTY OR PARISH 13. STATE

Lea

NM

4. PERMIT NO.

30-025-31617

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3780' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Run 5 1/2" casing and cement
(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

7. DESCRIBE PROMISED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).*

12/28/92 Drilled to 8850' TD. Ran 30 joints 5 1/2" 17# L80 casing and 184 joints 5 1/2" 17# J55 casing. Total 214 joints casing. Cemented at 8850' first stage with 600 sacks 50/50 Poz Mix, 5# salt, .3% Halaide-322, 10# Microbond and 1/4# Flocele per sack. Cement did not circulate. Plug down at 1:00 PM on 12/28/92. WOC. Released rig at 11:00 PM on 12/28/92.

01/05/93 Ran CBL from 6430' to 4400'. Perf 4 squeeze holes at 5380'. Squeeze cement with 300 sacks Hal Lite with 8# salt and 1/4# Flocele per sack, and 100 sacks Premium Plus with 2% CaCl. Displace cement to 5240' approx. WOC.

RECEIVED
FEB 1 9 37 AM '93
CARRIZO
AREA

18. I hereby certify that the foregoing is true and correct

SIGNED

Carol J. Sarai

TITLE

Production Supervisor

DATE

1/29/93

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR

(ORIG. SCD) DAVID R. GLASS
FEB 4 1993

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States a false statement.

RECEIVED

FEB 06 1993

CCD NUMBER 07106