

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240  
DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210  
DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31694
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2443
7. Lease Name or Unit Agreement Name Lotus ALT State
8. Well No. 2
9. Pool name or Wildcat Undes. Delaware
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3538' GR

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line Section 32 Township 22S Range 32E NMPM Lea County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 10:10 AM 9-19-92. Set 60' of 20" conductor and cemented to surface. Notified NMOCD, Hobbs, NM, of psud. Resumed drilling 17½" hole 6:45 PM 9-20-92. Ran 20 joints 13-3/8" 54.5# J-55 casing set 858'. Guide shoe set 858', insert float set 815'. Cmt'd w/575 sx PSL "C" + 2% CaCl2 (yield 1.75, wt 12.9). Tail in w/250 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 12:07 AM 9-22-92. Bumped plug to 500 psi, float held OK. Circulated 180 sacks cement. WOC. Drilled out 6:30 PM 9-22-92. WOC 18 hrs and 30 mins. NU and tested to 500 psi for 15 mins, OK. Reduced hole to 11" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 9-24-92  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE SEP 29 '92  
CONDITIONS OF APPROVAL, IF ANY:

**RECEIVED**

**SEP 28 1992**

**OCD HOBBS OFFICE**