

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department
OIL CONSERVATION DIVISION

Form C-103
Revised 1-1-89

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer Dd, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, Nm 87410

API NO. (assigned by OCD on New Wells)
30-025-3173-24
5. Indicate Type of Lease
STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
N/A
7. Lease Name or Unit Agreement Name
ARROWHEAD GRAYBURG UNIT
8. Well No.
190
9. Pool name or Wildcat
ARROWHEAD / GB
10. Elevation(Show whether DF, RKB, RT, GR, etc.)
3529' GE

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
CHEVRON U.S.A. INC.

3. Address of Operator
P.O. BOX 1150 MIDLAND, TX 79702 ATTN: P.R. MATTHEWS

4. Well Location
Unit Letter B : 760 Feet From The NORTH Line and 1890 Feet From The EAST Line
Section 11 Township 22S Range 36E NMPM LEA County

11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CMT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: <u>DRILLING SUMMARY</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations(Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU ROD-RIC #4 ON 10-12-92 AND SPUD 12 1/4" HOLE.
DRILL AND SURVEY FROM SURFACE TO 1445', TD 12.25" HOLE.
RUN 8 5/8" CASING TO 1445'. PUMP 900 SXS. OF CEMENT AND CIRCULATE 130 SXS. TO SURFACE.
WAIT ON CEMENT FOR 12 HOURS.
DRILL OUT FLOAT AND TEST CASING TO 1000# FOR 30 MIN.-OK.
DRILL AND SURVEY WITH 7.875" HOLE TO TD AT 4045'.
LOG HOLE.
RUN 5 1/2" CASING TO 4045' AND PUMP 750 SXS. CMT AND CIRC 66 SXS. TO SURFACE.
INSTALL WELLHEAD AND TEST-OK.
RELEASE RIG AT 10 PM ON 10-18-92.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNATURE <u>P.R. Matthews</u>	TITLE <u>TECH. ASSISTANT</u>	DATE: <u>10-19-92</u>
TYPE OR PRINT NAME <u>P.R. MATTHEWS</u>		TELEPHONE NO. <u>(915)687-7812</u>
APPROVED BY <u>Paul Kautz</u> Geologist	TITLE	DATE <u>OCT 21 '92</u>
CONDITIONS OF APPROVAL, IF ANY:		