Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION P.O. Box 2088

WELL API NO. 30–025–31762

ISTRICT II Santa Fe, New Mexic O. Drawer DD, Artesia, NM 88210	CO X/3U4-2UXX	
O. Diawei DD, Aicela, 1441 50210	00 0720 : 2000	5. Indicate Type of Lease STATE X FEE
OSTRICT III OOO Rio Brazos Rd., Aztec, NM 87410		6. State Oil & Gas Lease No. VB-134
SUNDRY NOTICES AND REPORTS ON W (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEF DIFFERENT RESERVOIR. USE "APPLICATION FOR (FORM C-101) FOR SUCH PROPOSALS.)	PEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
Type of Well: OIL GAS WELL X WELL OTHER		Kiwi AKX State
Name of Operator YATES PETROLEUM CORPORATION		8. Well No.
. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Pool name or Wildcat East Livingston Ridge Delaware
Well Location Unit Letter G : 1980 Feet From The North	Line and	980 Feet From The East Line
Section 16 Township 22S	Range 32E	NMPM Lea County
//////////////////////////////////////	ther DF, RKB, RT, GR, etc.) GR	
Check Appropriate Box to Indica NOTICE OF INTENTION TO:		, Report, or Other Data JBSEQUENT REPORT OF:
ERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
EMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILL	LING OPNS. PLUG AND ABANDONMENT
ULL OR ALTER CASING		
ULE ON ALTEN GASING	CASING TEST AND	CEMENT JOB []
		mediate Casing X
OTHER:	OTHER: Inter	mediate Casing X
THER:	OTHER: Inter ils, and give persinent dates, i and J-55 casts x PSL "C" + 2% wt 14.8). PD 7: cks cement. WOC	mediate Casing X including estimated date of starting any proposed g set 4610'. Float shoe set 4610' CaC12 (yield 1.76, wt 12.9). Tail 35 AM 11-8-92. Bumped plug to 160 Drilled out 2:45 AM 11-9-92.
THER: 12 Describe Proposed or Completed Operations (Clearly state all pertinent detainwork) SEE RULE 1103. 11-8-92. Ran 103 joints 8-5/8" 32# HC-8 Float collar set 4566'. Cemented w/1400 in w/250 sx "C" + 2% CaCl2 (yield 1.32, psi, float held okay. Circulated 190 sa WOC 18 hours and 10 mins. NU and tested	OTHER: Inter ils, and give persinent dates, i and J-55 casts x PSL "C" + 2% wt 14.8). PD 7: cks cement. WOC	mediate Casing X including estimated date of starting any proposed g set 4610'. Float shoe set 4610' CaC12 (yield 1.76, wt 12.9). Tail 35 AM 11-8-92. Bumped plug to 160 Drilled out 2:45 AM 11-9-92.
THER: 12 Describe Proposed or Completed Operations (Clearly state all pertinent detainwork) SEE RULE 1103. 11-8-92. Ran 103 joints 8-5/8" 32# HC-8 Float collar set 4566'. Cemented w/1400 in w/250 sx "C" + 2% CaCl2 (yield 1.32, psi, float held okay. Circulated 190 sa WOC 18 hours and 10 mins. NU and tested	OTHER: Inter ils, and give persinent dates, i and J-55 casts x PSL "C" + 2% wt 14.8). PD 7: cks cement. WOC	mediate Casing X including estimated date of starting any proposed g set 4610'. Float shoe set 4610' CaC12 (yield 1.76, wt 12.9). Tail 35 AM 11-8-92. Bumped plug to 160 Drilled out 2:45 AM 11-9-92.
THER: 12 Describe Proposed or Completed Operations (Clearly state all pertinent deta-work) SEE RULE 1103. 11-8-92. Ran 103 joints 8-5/8" 32# HC-8 Float collar set 4566'. Cemented w/1400 in w/250 sx "C" + 2% CaC12 (yield 1.32, psi, float held okay. Circulated 190 sa WOC 18 hours and 10 mins. NU and tested	OTHER: Inter ils, and give persinent dates, i and J-55 casts x PSL "C" + 2% wt 14.8). PD 7: cks cement. WOC	mediate Casing X including estimated date of starting any proposed g set 4610'. Float shoe set 4610' CaC12 (yield 1.76, wt 12.9). Tail 35 AM 11-8-92. Bumped plug to 160 Drilled out 2:45 AM 11-9-92.
THER: 12 Describe Proposed or Completed Operations (Clearly state all pertinent deta-work) SEE RULE 1103. 11-8-92. Ran 103 joints 8-5/8" 32# HC-8 Float collar set 4566'. Cemented w/1400 in w/250 sx "C" + 2% CaC12 (yield 1.32, psi, float held okay. Circulated 190 sa WOC 18 hours and 10 mins. NU and tested	OTHER: Inter ils, and give persinent dates, i and J-55 casts x PSL "C" + 2% wt 14.8). PD 7: cks cement. WOC	mediate Casing X including estimated date of starting any proposed g set 4610'. Float shoe set 4610' CaC12 (yield 1.76, wt 12.9). Tail 35 AM 11-8-92. Bumped plug to 160 Drilled out 2:45 AM 11-9-92.
THER: 12 Describe Proposed or Completed Operations (Clearly state all pertinent detamork) SEE RULE 1103. 11-8-92. Ran 103 joints 8-5/8" 32# HC-8 Float collar set 4566'. Cemented w/1400 in w/250 sx "C" + 2% CaC12 (yield 1.32, psi, float held okay. Circulated 190 sa WOC 18 hours and 10 mins. NU and tested	OTHER: Inter ils, and give pertinent dates, if 0 and J-55 casin sx PSL "C" + 2% wt 14.8). PD 7: cks cement. WOC to 1000 psi for	mediate Casing Including estimated date of starting any proposed g set 4610'. Float shoe set 4610' CaC12 (yield 1.76, wt 12.9). Tail 35 AM 11-8-92. Bumped plug to 160 Drilled out 2:45 AM 11-9-92. 15 mins. Reduced hole to 7-7/8"
THER: 12 Describe Proposed or Completed Operations (Clearly state all pertinent detainwork) SEE RULE 1103. 11-8-92. Ran 103 joints 8-5/8" 32# HC-8 Float collar set 4566'. Cemented w/1400 in w/250 sx "C" + 2% CaC12 (yield 1.32, psi, float held okay. Circulated 190 sa WOC 18 hours and 10 mins. NU and tested resumed drilling.	OTHER: Inter ils, and give pertinent dates, if 0 and J-55 casin sx PSL "C" + 2% wt 14.8). PD 7: cks cement. WOC to 1000 psi for	mediate Casing Including estimated date of starting any proposed g set 4610'. Float shoe set 4610' CaC12 (yield 1.76, wt 12.9). Tail 35 AM 11-8-92. Bumped plug to 160 Drilled out 2:45 AM 11-9-92. 15 mins. Reduced hole to 7-7/8"
12. Describe Proposed or Completed Operations (Clearly state all pertinent detainwork) SEE RULE 1103. 11-8-92. Ran 103 joints 8-5/8" 32# HC-8 Float collar set 4566'. Cemented w/1400 in w/250 sx "C" + 2% CaCl2 (yield 1.32, psi, float held okay. Circulated 190 sa WOC 18 hours and 10 mins. NU and tested resumed drilling.	OTHER: Inter ils, and give persinent dates, is 0 and J-55 casin sx PSL "C" + 2% wt 14.8). PD 7: cks cement. WOC to 1000 psi for	mediate Casing Including estimated date of starting any proposed g set 4610'. Float shoe set 4610' CaC12 (yield 1.76, wt 12.9). Tail 35 AM 11-8-92. Bumped plug to 160 Drilled out 2:45 AM 11-9-92. 15 mins. Reduced hole to 7-7/8"
12. Describe Proposed or Completed Operations (Clearly state all pertinent detainwork) SEE RULE 1103. 11-8-92. Ran 103 joints 8-5/8" 32# HC-8 Float collar set 4566'. Cemented w/1400 in w/250 sx "C" + 2% CaCl2 (yield 1.32, psi, float held okay. Circulated 190 sa WOC 18 hours and 10 mins. NU and tested resumed drilling.	OTHER: Inter ils, and give persinent dates, is 0 and J-55 casin sx PSL "C" + 2% wt 14.8). PD 7: cks cement. WOC to 1000 psi for	mediate Casing X Including estimated date of starting any proposed Supervisor DATE Table

DEC 0 % 1992 OCD HOBBS OFFICE

RECEIVED