

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31762
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-134
7. Lease Name or Unit Agreement Name Kiwi AKX State
8. Well No. 7
9. Pool name or Wildcat East Livingston Ridge Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION	3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter <u>G</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>16</u> Township <u>22S</u> Range <u>32E</u> NMPM Lea County		
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3769' GR		

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production Casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8900'. Reached TD 10:15 AM 11-15-92. Ran 199 joints 5-1/2" 15.5# and 17# J-55 casing set 8900'. Float shoe set 8900', float collar set 8855'. DV tool set 7729'. Cemented in two stages. Stage 1: 140 sx "H" + 8#/sx CSE + 5#/sx Gilsonite + .06% CF-14 + .35% Thriftylite (yield 1.75, wt 13.6). Tailed in w/80 sx "H" + 10% Thixad + 10% Salt + 8#/sx Hiseal (yield 1.38, wt 15.5). PD 7:36 PM 11-16-92. Bumped plug to 1100 psi for 1 min. Circulated 51 sacks cement. Circulated thru DV tool 3 hours. Stage 2: 600 sx PSL "C" + 5#/sx Gilsonite + 5#/sx Salt + .04% CF-14 (yield 2.04, wt 12.5). Tailed in w/200 sx "H" + 8#/sx CSE + 5#/sx Gilsonite + .6% CF-14 + .35% Thriftylite. PD 11:45 PM 11-16-92. Bumped plug to 3000 psi for 1 min. WOC 18 hours.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 11-18-92
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

NOV 23 '92

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

NOV 2 6 1992

Q20 PACE OF GROWTH