	UNITED °	SATES	OFFICE FOR NUMBER OFFICE FOR NUMBER OF COPIES REOUIRFI (Other linetructions of	424 Across11 i Modified For NN060-3160-4	n No.	
July 1989) Entropy 9-331) DEPARTMENT C		HE INTERIOR	(Other Instructions o verse side)	LEASE DESIGNAT	TION AND BRIAL NO.	
S (De not US	BUREAU OF LAND UNDRY NOTICES AND this form for proposals to drill or t Use "APPLICATION FOR PER	REPORTS ON	WEELS		TTEE OR TRIBE NAME	
(1)8 161 0	Use "APPLICATION FOR PER	EB	EP. WY SE 6 1	7. UNIT AGREEMEN	TNAME	
WELL	A OTHER	CAE	3n. Aren Code & Pho	DE NO. 8. PARM OR LEASE		
Strata Pro	oduction Company	AREA	1	27 Lechuza	Federal	
P. O. Box 1030, Roswell, New Mexico 88202-1			30	#4	#4	
1. LOCATION OF WRLL (Report location clearly and in accordance with any S See also space 17 below.) At surface			requirements.*	Livingst	10. FIELD AND FOOL, OB WILDCAT Livingston Ridge Delaware East 11. SBC., T., R., M., OR BLK. AND	
Unit N	660' FSL & 1650'	FWL		Section	15-22S-32E	
14. PERMIT NO.	15. ELEVATION	IS (Show whether DF, RT,	GR. etc.)	12. COUNTY OF PA	ARISH 13. STATE	
30-025-31		3703' GL		Lea	NM	
16.	Check Appropriate Bo	x To Indicate Natur		, or Other Data JUBSEQUENT REPORT OF:		
	NOTICE OF INTENTION TO:		WATER SRUT-OFF		LING WELL	
TEST WATER ST PRACTURE TREA			FRACTURE TREATMEN		ING CABING	
SHOOT OR ACID	IZR ABANDON*		SHOOTING OR ACIDIZI	/8 th casing and c	cement X	
REPAIR WELL (Other)	CHANGE PLANS		(Note: Report Completion or 1	results of multiple completion Report and L	etion on Well og form.)	
17. DESCRIBE PROPO proposed wor	NED OR COMPLETED OPERATIONS (Clear re. If well is directionally drilled. g rork.)*					
1/3/93	Drilled into water fl H ₂ S equipment.					
1/5/93	Drilled to 4481'. Ran 62 joints 8 5/8" 32# J55 casing and 45 joints 8 5/8" 24# J55 casing. Cemented at 4481' first stage with 175 sacks Hal Lite with 15# salt and 1/4# Flocele per sack. Circulated 125 sacks to pit. Tail in with 200 sacks Class "C" with 2% CaCL. Cemented second stage with 725 sacks Hal Lite with 15# salt and 1/4# Flocele per sack. Tail in with 100 sacks Class "C" Neat. Did not circulate to pit. Perf at 2800'. Squeeze cement with 800 sacks Hal Lite with 15# salt and 1/4# Flocele per sack. Tail in with 100 sacks Class "C" Neat with 2% CaCL. Plug down at 10:15 AM on 1/6/93.					
1/7/93	Ran Temp survey. Tag with 300 sacks Hal Li 200 sacks Class "C" M down at 7:45 AM on 1/	te with 10# sa	Cl Circulate	d 111 sacks ceme	ent to pit. Plug	
			ACORE	Contraction and	1	
			(ORIC	SCOL BOOTED		
				3354 8931D R.	HASS	
18. I hereby certif	y that the foregoing is prue and cor	rect		Can	1/29/93	
SIGNED	ard J. Dara	TITLE Proc	luction Supervi	SUI DATE		
(This space fo	or Federal or State office use)					
APPROVED B		TITLE	······	DATE		
CONDITIONS	OF APPROVAL, IF ANY :					

*See Instructions on Reverse Side