

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL & 660' FWL, Section 25, T22S, R32E

CONFIDENTIAL

Unit D

5. Lease Designation and Serial No.

NM-2379

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Covington A Federal No.2

9. API Well No.

30-025-31850

10. Field and Pool, or Exploratory Area

Red Tank Bone Spring

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other TD & Prod Csg

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled 7-7/8" hole to 10,120'. TD reached 0215 hrs CST 12/7/93. Logged well w/ Schlumberger. Ran 233 jts 5-1/2", 17#, J-55 & N-80, LT&C casing. Float shoe @ 10,120'. Float collar @ 10,075'. Stage tool @ 6611'. Howco cemented 1st stage w/860 sx Class "H" + 5% Microbond + 2.4 pps KCl + .6% H-322 @ 15.6 ppg. Landed plug. Dropped bomb & opened DV tool @ 6611'. Circulated 5 hrs between stages. Recovered 93 sx excess cement. Cemented 2nd stage w/ 750 sx Class "C" + 12 pps Gilsonite + 2.8 pps KCl + .3% H-322 + .3% H-344 @ 14.1 ppg. Plug down @ 2245 hrs CST 12/8/93. ND BOP's. Set slips and make cut-off. Weld on wellhead and test to 2000 psi.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Senior Operations Engineer

Date Jan. 17, 1994

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____