June 1990)	DEPARTMENT OF BUREAU OF LAN		FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE			NM-70343 6. If Indian, Allottee or Tribe Name	
			7. If Unit or CA, Agreement Designation	
1. Type of Well			8. Well Name and No.	
2. Name of Operator	Other		Dagger Lake "8" Fed.	
Meridian Oil Inc.			9. API Well No.	
3. Address and Telephone No.			30-025-31885	
P.O. Box 51810, Midland, TX 79710-1810 915-688-6800			10. Field and Pool, or Exploratory Area	
4 Location of Well (Footage, Sec., T., R., M., or Survey Description)			Dagger Lake Delaware	
C, 660' FNL & 1980' FWL Sec. 8, T22S, R33E			11. County or Parish, State Lea	
2 CHECK	APPROPRIATE BOX(s) TO	O INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA	
TYPE OF	SUBMISSION	TYPE OF ACTION		
Notice	of Intent		Change of Plans	
Subseq		Recompletion Plugging Back	New Construction	
Subseq	luent Report		Water Shut-Off	
Final A	Abandonment Notice	Altering Casing	Conversion to Injection	
		X Other set casing	Dispose Water (Note: Report results of multiple completion on Wi Completion or Recompletion Report and Log form	
give subsurface lo	cations and measured and true vertical dep	the for all markers and zones pertinent to this work.)*		
give subsurface lo	- rig up and spud 12½ - run 14 jts. 8 5/8" circulate csg.			
give subsurface lo	- rig up and spud 12¼ - run 14 jts. 8 5/8" circulate csg. cmt. w/375 sxs. cla	" hole csg set @633'.		
give subsurface lo	- rig up and spud 12¼ - run 14 jts. 8 5/8" circulate csg. cmt. w/375 sxs. cla	" hole csg set @633'.		
1-27-93	- rig up and spud 12¼ - run 14 jts. 8 5/8" circulate csg. cmt. w/375 sxs. cla	" hole csg set @633'. ss "C" w/2% CaCl2. circ. 115 sxs.		
give subsurface lo 1-27-93 1-28-93	- rig up and spud 12¼ - run 14 jts. 8 5/8" circulate csg. cmt. w/375 sxs. cla	" hole csg set @633'. ss "C" w/2% CaCl2. circ. 115 sxs.		
give subsurface lo 1-27-93 1-28-93	- rig up and spud 12¼ - run 14 jts. 8 5/8" circulate csg. cmt. w/375 sxs. cla woc 4.25 hrs.	" hole csg set @633'. ss "C" w/2% CaCl2. circ. 115 sxs.		
give subsurface lo 1-27-93 1-28-93 1-28-93 1-28-93	- rig up and spud 12 ¹ / ₄ - run 14 jts. 8 5/8" circulate csg. cmt. w/375 sxs. cla woc 4.25 hrs.	" hole csg set @633'. ss "C" w/2% CaCl2. circ. 115 sxs.	<u>2-17-93</u>	

H

*See instruction on Reverse Side

RECEIVED

MAR 0 & 1993

OCH HORRE A-----