Yates Petroleum Corporation Kiwi AKX State #8 F- 16-T22S-R32E

Attachment A Page 1

III. Well Data

- A. 1. Lease Name/Location: Kiwi AKX State #8 F-16-T22S-R32E 1980' FNL & 2310' FWL
 - 2. Casing Strings:
 - a. Present Well Condition
 13 3/8", 54.5#, J55 @ 850' w/800 sx (circ)
 8 5/8", 32#, HC-80, J55 @ 4590' w/1800 sx.
 5 1/2", 15.5#, 17#, N80, J55 @ 8840' w/1355 sx (TOC 3900' CBL)
 Present Status:
 Non-commercial completion in Delaware at 8443'-8470', 8539'-8562' and 8653'-8710'.
 - 3. Proposed well condition: Casing same as above.
 3 1/2" 9.3 J55 or 2-7/8" 6.5 J55 plastic-coated injection tubing @ 5150'.
 - 4. Propose to use Guiberson or Baker plastic-coated or nickel-plated packer set at 5150'.
- B. 1. Injection Formation: Delaware Sand
 - 2. Injection Interval will be through perforations from approximately 5240' 8710' gross interval.
 - 3. Well was originally drilled as a Delaware Sand oil well. Well will be Delaware Sand water disposal well (5240'-8710') when work is completed.
 - 4. Perforations: High porosity sands to be selected between 5240' and 8710', including current zones 8443'-8470', 8539'-8562' and 8653'-8710'.
 - 5. Next higher (shallower) oil or gas zone within 2 miles--None. Next lower (deeper) oil or gas zone within 2 miles--Bone Spring.