

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		WELL API NO. 30-025-31889
2. Name of Operator YATES PETROLEUM CORPORATION		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
3. Address of Operator 105 South 4th St., Artesia, NM 88210		6. State Oil & Gas Lease No. VB-134
4. Well Location Unit Letter <u>F</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>2310</u> Feet From The <u>West</u> Line Section <u>16</u> Township <u>22S</u> Range <u>32E</u> NMPM Lea County		7. Lease Name or Unit Agreement Name Kiwi AKX State
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3746' GR		8. Well No. 8
		9. Pool name or Wildcat East Livingston Ridge Delaware

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production Casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8840'. Reached TD 2-26-93. Ran 215 joints 5-1/2" 15.5# and 17# J-55 and N-80 casing set 8840'. Float shoe set 8840', float collar set 8798'. DV tool set 6386'. Short joint set 7978'. Cemented in 2 stages. Stage I: 460 sx "H" + 8#/sx CSE + 5#/sx Gilsonite + 0.6% CF-14 + .35% Thriftylite (yield 1.84, wt 13.6). Tailed in w/65 sx "H" + 10% Thixad + 8#/sx Hiseal + 10% Salt (yield 1.38, 25 14.4). PD 1:30 AM 2-28-93. Bumped plug to 1500psi for 5 mins. Circulated 90 sacks. Circulated through DV tool 4 hrs. Stage II: 370 sx PSL "C" + 5#/sx Gilsonite + 0.4% CF-14 + 5#/sx salt (yield 1.85, wt 12.7). Tailed in w/460 sx "H" + 8#/sx CSE + 5#/sx Gilsonite + 0.6% CF-14 + 0.35 % Thriftylite (yield 1.75, wt 13.6). PD 6:31 AM 2-28-93. PD 6:30 AM 2-28-93. Bumped plug to 2500 psi for 5 minutes. WOC 18 hrs. Drilled out DV tool at 6386'. Tagged PBDT at 8794'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-4-93

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Paul Kanta TITLE Geologist DATE MAR 08 1993

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR 05 1962

OCD HOBBS OFF