Submit 3 Copies lo Dis

APPROVED BY --

CONDITIONS OF APPROVAL, IF ANY:

## Ttate of New Mexico

Form C-103

lo Appropriate District Office	Energy, Mine. s and Natural Resources Department		Revised 1-1-89 ,
OIL CONSERVATION DIVISION P.O. Box 2088		WELL API NO. 30-025-31889	
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease  STATE X FEE
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410			6. State Oil & Gas Lease No. VB-134
SUNDRY NOTICES AND REPORTS ON WELLS  ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name
1. Type of Well: Oil. OAS WELL X WELL	OTHER		Kiwi AKX State
Name of Operator YATES PETROLEUM CORPORATION			8. Well No.
3. Address of Operator			9. Pool name or Wildcat
105 South 4th St., Ar	tesia, NM 88210	·	East Livingston Ridge Delaware
• /	80 Feet From The North		_
Section 16	Township 22S Ran  10. Elevation (Show whether I	nge 32E	NMPM Lea County
	3746 G		
Check	Appropriate Box to Indicate N		Report or Other Data
	** *		BSEQUENT REPORT OF:
NOTICE OF INTENTION TO:			DOEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
EMPORARILY ABANDON L CHANGE PLANS L COMMENCE DRILLIN		IG OPNS. X PLUG AND ABANDONMENT	
PULL OR ALTER CASING	ULL OR ALTER CASING CASING TEST AND C		EMENT JOB X
OTHER:		OTHER: Ran sur	face & intermediate casing X
work) SEE RULE 1103.  Spudded 26" hole 1:0  Joan, NMOCD, Hobbs,  13-3/8" 54.5# J-55 c  w/550 sx PSL "C" w/2  1.32, wt 14.8). PD  sacks. WOC. Drille  500 psi for 15 minut  2-19-93. Ran 112 jc  Float collar set 454  1.98, wt 12.8). Tai  Bumped plug to 1800	OO PM 2-8-93. Set 40' of NM, of spud. Resumed dreasing, set 850'. Guide 2% CaC12 (yield 1.76, wt 7:35 AM 2-14-93. Bumped dout 3:15 AM 2-15-93. Ses, OK. Reduced hole to bints 8-5/8" 32# HC-80 are 49'. Cemented w/1600 sx alled in w/200 sx "C"+ 2% psi, float held OK. Circuminutes. NU and tested	shoe set 850', 12.9). Tail is plug to 600 p WOC 19 hours a 11" and resumend J-55 casing PSL "C" + 10#/CaC12 (yield loulated 175 sac	Redi-mix to surface. Notified hole 6:00 AM 2-13-93. Ran 19 joints insert float set 806'. Cemented m w/250 sx Class "C" w/2% CaCl2 (yields, float held OK. Circulated 125 and 40 minutes. NU and tested to ed drilling. set 4590'. Float shoe set 4590'. Sx Salt + 1/4#/sx Celloseal (yield32, wt 14.8). PD 10:20 PM 2-19-93. Eks. WOC. Drilled out 4:30 PM 2-20-pr 15 minutes, OK. Reduced hole to
I hereby certify that the information above is	true and complete to the best of my knowledge and	I belief.	
SIGNATURE Canita	Dordled II	Production	Supervisor DATE 3-4-93
TYPE OF FRINT NAME Juani	ita Goodlett		тецерноме no. 505/748-1471
(This space for State Use)	Orig. Signed by Paul Kautz		17.0 0 8 <b>1903</b>
ATERONIES BY	Geologist	n.e	DATE

– mre –

\_\_\_\_ DATE ---

RECEIVED

OCD HOBBS OFFICE