

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget: Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM-77060

6. If Indian, Allottee or Tribe Name

7. If Unit or C.A. Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FEL, Sec. 34, T22S, R32E

8. Well Name and No.

Red Tank 34 Federal #2

9. API Well No.

30-025-31932

10. Field and Pool, or Exploratory Area

Red Tank Delaware, West

11. County or Parish, State

Lea, New Mexico

**CONFIDENTIAL**

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other TD & Production Csg

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Exeter 66 Drilled 7-7/8" hole 4570 to 8900. TD reached 15:30 hrs CDT 9-25-93. Logged w/ Schlumberger. Ran 202 jts 5-1/2" 17# N-80 & J-55 casing. Stage tool @ 5866. Shoe @ 8900, FC @ 8853. Haliburton cmt'd 1st stage w/ 155 sxs lite 12.7 ppg. Tailed w/ 730 sxs silicalite Premium "C" 13.6 ppg. Open tool @ 5866. Circ'd 5 hrs between stages. Recovered 250 sxs excess. Cmt'd 2nd stage w/ 190 sxs lite 12.7 ppg. Tailed w/ 395 sxs "C" w/ 8#/sx silicalite 13.6 ppg. Job complete 9-27-93. TOC 2070'.

14. I hereby certify that the foregoing is true and correct

Signed Barnet L. Smith Title Senior Operations Engineer

Date Nov. 17, 1993

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_ Date \_\_\_\_\_