

Form 3160-5
(June 1990)

RECEIVED
MAR 23 11 08 AM '94
OAR
AELA

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
MAR 25 3 25 PM '94
BUREAU OF LAND MANAGEMENT
HOBBS, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or to enter to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

U. S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NEW MEXICO
P.O. BOX 1980
HOBBS, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-77060

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Red Tank 34 Federal No. 3

9. API Well No.

30-025-31951

10. Field and Pool, or Exploratory Area

W. Red Tank Delaware

11. County or Parish, State

Lea County, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

760' FNL & 660' FEL, Section 34, T22S, R32E

CONFIDENTIAL

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other: Spud & Set Surface Csg

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU Grace Rig #353. Spud well @ 1700 hrs CST 2/8/94. Drilled 17-1/2" hole to 770'. TD reached @ 1400 hrs CST 2/9/94. Ran 17 jts 13-3/8", 54.5#, J-55, ST&C casing. TPGS @ 770'. IFV @ 724'. Howco cemented casing w/ 750 sx Halliburton Lite @ 12.7 ppg followed by 200 sx Class "C" + 2% CaCl₂ @ 14.8 ppg. Plug down @ 2100 hrs CST 2/9/94. Recovered 200 sx excess cement. WOC 18 hrs. Cement has a compressive strength over 500 psi after 8 hrs. Make cut-off. Weld on wellhead and test to 500 psi. NU BOP's and test to 2000 psi.

J. L. Lora
MAR 12 1994

14. I hereby certify that the foregoing is true and correct

Signed

Title Senior Operations Engineer

Date March 23, 1994

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side