

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.  
NM-77060

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

CONFIDENTIAL

2. Name of Operator  
Pogo Producing Company

3. Address and Telephone No.  
P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
760' N 330' E & 2310' FEL, Sec. 28, T23S, R32E

8. Well Name and No.  
Red Tank 34 Federal No. 3

9. API Well No.  
30-025-31951

10. Field and Pool, or Exploratory Area  
Red Tank Bone Spring

11. County or Parish, State  
Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other TD & Production Csg  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 7-7/8" hole from 770' to 8750'. TD reached @ 1600 hrs CST 2/24/94. Logged well w/ Schlumberger. Ran 199 jts 5-1/2", 17#, J-55 & L-80, LT&C casing. Guide shoe @ 8750'. Float collar @ 8705'. Casing packer @ 6372'. Stage tools 4613' & 6370'. Howco cemented 1st stage w/ 515 sx Class "H" + 5 pps Microbond + 2.4 pps KCl + .6% H-322 @ 15.6 ppg. Drop plug and displace cement. Drop bomb and open DV tool @ 6370'. Circulate 4 hrs between stages. Recovered 80 sx excess cement. Cement 2nd stage w/ 390 sx Class "C" + 12 pps Gilsonite + 2.8 pps KCl + .3% H-322 + .3% H-344 @ 14.1 ppg. Drop plug and displace cement. Drop bomb and open DV tool @ 4613'. Circulate 5 hrs between stages. Recovered 140 sx excess cement. Cement 3rd stage w/ 1535 sx Halliburton Lite @ 12.7 ppg followed by 100 sx Class "C" @ 14.8 ppg. ND BOP's and make cut-off. Weld on wellhead and test to 2000 psi.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Senior Operations Engineer Date March 23, 1994

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_  
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

**RECEIVED**

**MAR 24 1994**

**U.S. DEPT. OF JUSTICE  
OFFICE**