			•
Form 3160-5 (June 1990)	DEPARTMEN	ED STATES T OF THE INTERIOR AND MANAGEMENT	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. NM-77060
Do not use this fo	orm for proposals to dril	AND REPORTS ON WELLS If or to deepen or reentry to a different reservoir. I PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name
	SUBMIT	7. If Unit or CA, Agreement Designation	
I. Type of Well XVOil Gas Well Weil	Other	CONFIDENTIAL	8. Weil Name and No.
2. Name of Operator Pogo Producing	g Company		Red Tank 34 Federal No. 4
<ol> <li>Address and Telephone No.</li> <li>P. O. BOX 10340, Midland, TX 79702-7340</li> <li>4. Location of Weil (Footage, Sec., T., R., M., or Survey Description)</li> </ol>			30-025-32136 10. Field and Pool, or Exploratory Area Red Tank Bone Springs 11. County or Parish, State
32 1980' FNL & 1980' FEL, Section 34, T22S, R34E			Lea County, NM
I2. CHECK	APPROPRIATE BOX(s	) TO INDICATE NATURE OF NOTICE, REPOR	IT, OR OTHER DATA
TYPE OF	SUBMISSION	TYPE OF ACTION	····-
	of Intent ent Report pandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other III termediate	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Weil Completion or Recompletion Report and Log form.)
13. Describe Proposed or Con give subsurface loca	mpleted Operations (Clearly state all tions and measured and true vertical	pertinent details, and give pertinent dates, including estimated date of starting depths for all markers and zones pertinent to this work.)*	any proposed work. If well is directionally drilled,
8-5/8", packer @ Lite @ 12 land plug Lite @ 12 CST 1/27	32#, J-55, ST&C ca 3389'. DV tool @ 2.7 ppg followed b g. Drop bomb and 2.7 ppg followed b /94. Recovered 15	570'. TD reached @ 1445 hrs CST 1/26 sing. Float shoe @ 4570'. Float col 3386'. Howco cemented 1st stage w/ y 200 sx Premium Plus @ 14.8 ppg. Di open DV tool. Cement 2nd stage w/ 14 y 50 sx Premium Plus @ 14.8 ppg. Plu 0 sx excess cement. ND BOP's and mak 00 psi. NU BOP's and test to 1500 ps	lar @ 4523'. Casing 100 sx Halliburton splace cement and 00 sx Halliburton g down @ 0800 hrs e cut-off. Weld

14. I hereby certify in the foregoing is the and forreer Signed	Tide Senior Operations Engineer	DateMarch 28, 1994
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Tide	Date
Title 18 U.S.C. Section 1001, makes it a crime for any person kno or representations as to any matter within its jurisdiction.	wingly and willfully to make to any department or agency of the United Sta	ates any false, fictitious or fraudulent statements



----

1