

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

CONFIDENTIAL

2. Name of Operator
Pogo Producing Company

3. Address and Telephone No.
P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1980' FSL & 660' FEL, Section 27, T22S, R32E

5. Lease Designation and Serial No.
NM-81272

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. Exxon 27
Prize Federal No. 3

9. API Well No.
30-025-32143

10. Field and Pool, or Exploratory Area
Red Tank Bone Springs

11. County or Parish, State
Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other TD & Production Csg

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to 8855'. TD reached 0930 hrs CST 11/19/93. Logged well with Schlumberger. Ran 202 jts 5-1/2", 17#, J-55 & N-80, LT&C casing. Float shoe @ 8855'. Float collar @ 8809'. DV tool @ 6611'. Howco cemented 1st stage with 575 sx Class "H" + 5 pps microbond + 2.4 pps KCL + 6% Halad 322 @ 15.6 ppg. Drop plug. Float held. Drop bomb and open DV tool. Circulate 5 hrs between stages. Recover 132 sx excess cement. Cement 2nd stage with 850 sx Class "C" + 12 pps Gilsonite + 2.8 pps KCL + .3% Halad 322 + .3% Halad 344. Plug down and close tool @ 2130 hrs CST 11/20/93. Set slips and make cut-off. ND BOP's. Weld on wellhead and test to 1500 psi. TOC @ 2240'.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Senior Operations Engineer Date 12/8/93

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side