

CTI
Box 1980, Hobbs, NM 88240

ICT II
Drawer DD, Artesia, NM 88210

RICT III
Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

| |
|---|
| WELL API NO. 30-025-32255 |
| 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. VB-0134 |
| 7. Lease Name or Unit Agreement Name Kiwi AKX State |
| 8. Well No. 9 |
| 9. Pool name or Wildcat East Livingston Ridge Delaware |

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
YATES PETROLEUM CORPORATION

Address of Operator
105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Well Location
Unit Letter A : 330 Feet From The North Line and 330 Feet From The East Line

Section 16 Township 22S Range 32E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3781' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

| | | | |
|--|---|---|---|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | | CASING TEST AND CEMENT JOB <input type="checkbox"/> | |
| OTHER: <input type="checkbox"/> | | OTHER: <u>Intermediate Casing</u> <input checked="" type="checkbox"/> | |

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-20-93. Ran 103 joints 8-5/8" 32# J-55 casing set 4607'. Guide shoe set 4607'. Float collar set 4563'. Cemented w/1500 sx PSL "C" w/10#/sx Salt, 1/4#/sx Celloseal (yield 1.98, wt 12.8). Tailed in w/200 sx Class "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 8:45 PM
10-20-93. Bumped plug to 1500 psi, float held OK. Circulated 200 sacks cement, but lost returns before PD. Cement fell back to 660'. WOC 5 hours. Ran Temperature Survey and TOC at 650'. Ran 1". Spotted 200 sx Class "C" Neat. PD 5:10 AM 10-20-93. WOC. Drilled out 5:30 PM 10-21-93. WOC 20 hours and 45 minutes. Reduced hole and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 10-22-93
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE OCT 27 1993

CONDITIONS OF APPROVAL, IF ANY: