

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO. 30-025-32331
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. V-4082
7. Lease Name or Unit Agreement Name WILD TURKEY "10" STATE
8. Well No. 1
9. Pool name or Wildcat LIVINGSTON RIDGE; DELAWARE E.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐					
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OTHER ☐					
2. Name of Operator MARALO, INC.					
3. Address of Operator P. O. BOX 832, MIDLAND, TX 79702					
4. Well Location Unit Letter L : 1980 Feet From The SOUTH Line and 330 Feet From The WEST Line Section 10 Township 22S Range 32E NMPM LEA County					
10. Date Spudded 4-19-95	11. Date T.D. Reached 05-10-95	12. Date Compl. (Ready to Prod.) 06-10-95	13. Elevations (DF & RKB, RT, GR, etc.) 3792.4' GR	14. Elev. Casinghead	
15. Total Depth 9000'	16. Plug Back T.D. 7325'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By Rotary Tools 0-TD	Cable Tools	
19. Producing Interval(s), of this completion - Top, Bottom, Name 7168 - 7175' DELAWARE				20. Was Directional Survey Made YES	
21. Type Electric and Other Logs Run GR/CNL/LDT/ATT, GR/CBL/CCL				22. Was Well Cored YES	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	54.5#	1118'	17-1/2"	1000 SXS CL. "C"	
8-5/8"	32.0#	4700'	12-1/4"	1ST STG: 1970 HALCO LT + 250 PREM	
				2ND STG: 1000 HALCO LT + 100 PREM	
5-1/2"	17.0#	9000'	7-7/8"	375 SXS HALCO LT + 725 50/50 POZ	
24. LINER RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	
			25. TUBING RECORD		
			SIZE	DEPTH SET	PACKER SET
			2-7/8"	7122'	-
26. Perforation record (interval, size, and number) 7400 - 7475' (10 HOLES) 7168 - 7175' (15 HOLES)			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL BOTH AMOUNT AND KIND MATERIAL USED 7400 - 7475' & 7168 - 7175' 42,000# 16/30 SD + 8000# 16/30 RESIN SD. 7475' 5 1/2" CIBP @ 7463' W/10' CNT CAP 5 1/2" CIBP @ 7360' W/35' CNT CAP		
28. PRODUCTION					
Date First Production 06/10/95		Production Method (Flowing, gas lift, pumping - Size and type pump) PUMPING 2 1/2" X 1-3/4" X 24' PUMP			Well Status (Prod. or Shut-in) PROD.
Date of Test 08/23/95	Hours Tested 24	Choke Size -	Prod'n For Test Period	Oil - Bbl. 19	Gas - MCF 18
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl. 322
				Oil Gravity - API - (Corr.) 38.6	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD					Test Witnessed By PHILLIP SMITH
30. List Attachments DEVIATION SURVEY, LOGS (2) C-104, TEMPERATURE SURVEY					

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Dorothea Logan Printed Name DOROTHEA LOGAN Title REGULATORY ANALYST Date 08/29/95

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____	T. Canyon _____
T. Salt _____	T. Strawn _____
B. Salt _____	T. Atoka _____
T. Yates _____	T. Miss _____
T. 7 Rivers _____	T. Devonian _____
T. Queen _____	T. Silurian _____
T. Grayburg _____	T. Montoya _____
T. San Andres _____	T. Simpson _____
T. Glorieta _____	T. McKee _____
T. Paddock _____	T. Ellenburger _____
T. Blinebry _____	T. Gr. Wash _____
T. Tubb _____	T. Delaware Sand <u>4908'</u>
T. Drinkard _____	T. Bone Springs <u>8798'</u>
T. Abo _____	T. _____
T. Wolfcamp _____	T. _____
T. Penn _____	T. _____
T. Cisco (Bough C) _____	T. _____

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todilto _____	T. _____
T. Entrada _____	T. _____
T. Wingate _____	T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____	No. 3, from _____ to _____
No. 2, from _____ to _____	No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____	feet _____
No. 2, from _____ to _____	feet _____
No. 3, from _____ to _____	feet _____

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
150	735	585	SURF & REDBED				
735	936	201	ANHY				
936	1118	182	ANHY & REDBED				
1118	1730	1614	LIME				
1730	2775	1045	SALT, ANHY & LIME				
2775	3510	735	ANHY & LIME				
3510	4585	1075	LIME				
4585	4700	115	LIME & ANHY				
4700	5110	410	LIME				
5110	6180	1070	SAND				
6180	7065	885	SAND & SHALE				
7065	7743	678	SAND & LIME				
7743	9000	1257	SAND & SHALE				
9000			SAND & LIME				

RECEIVED