Submit 3 Copies to Appropriate District Office

State of New Mexico Energy Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION P.O. Box 2088

310)-025-32331	 	
5.	Indicate Type of Lease STATE XX	FEE	

WELL API NO.

DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico		
	Bana re, rien rize, ze	0/304-2000	5. Indicate Type of Lease STATE XX FEE
DISTRICT III			6. State Oil & Gas Lease No.
1000 Rio Brazos Rd., Aztec, NM 87410			o. Sait on a said
SUNDRY NOTICES A	ND REPORTS ON WEL	LS	
LDO NOT USE THIS FORM FOR PROPOSAL	S TO DRILL OR TO DEEPEN	OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. (JSE *APPLICATION FOR PE R SUCH PROPOSALS.)	RMIT"	
. Type of Well:			
OIL GAS WELL MELL	OTHER		WILD TURKEY "10" STATE
Name of Operator			8. Well No.
MARALO, INC. Address of Operator			9. Pool name or Wildcat
P. O. BOX 832, MIDLAND, TX 7970	2		
Well Location			UFCT
Unit Letter L : 1980 Fee	t From The SOUTH	Line and330	Feet From The MESI Line
Section 10 Tov	vnship 22S Ra		NMPM LEA County
36CHOII 108	10. Elevation (Show whether	DF, RKB, RT, GR, etc.)	\/////////////////////////////////////
	3792.4' G		
1. Check Approp	oriate Box to Indicate	Nature of Notice, R	eport, or Other Data
NOTICE OF INTENTI	ON TO:	SUB	SEQUENT REPORT OF:
ERFORM REMEDIAL WORK PL	UG AND ABANDON	REMEDIAL WORK	ALTERING CASING
		COMMENCE DRILLING	GOPNS. PLUG AND ABANDONMENT
EMPORARILY ABANDON C	HANGE PLANS		
JLL OR ALTER CASING		CASING TEST AND CE	f.
THER:		OTHER:	COMPLETION
WALL SEE BILLE 1103			
COMPLETION OPERATION: 05/24/95 ITS 2-7/8" TBG TO 8948'PBTD TBG TAI 05/25/95 RU BJ SERVICES & SPOTTED CCL, LOGGED FROM 8943' PBTD ML TO 0 7400', 7402', 7404", 7409', 7415 & TESTED TO 7500 PSI ABOVE SLIPS MI 2-7/8" TBG TO 7306'. ND BOP. SET TIED ONTO TBG & PRESSURED UP TO 16 CONTINUE TREATMENT OF PERFS BY PUM 3.2 BPM.	HAD 290 JTS 2-7/8" TBG LLEY. PICKLED TBG W/2 200 GALS MUD CLEAN OU TOC @ 3500' W/1000 PSI ', 7417', 7422', 7426' HILE RUNNING IN HOLE W PKR W/20 POINTS COMPR BO PSI, & FORMATION BE PING 750 GALS 7-1/2% P	UNLOADED ONTO PIPE OO GALS 7-1/2" NEFE OT ACID TRIP. INHIBI ON CSG. RIH W/4" , 7431', 7475'. TOT 1/2-3/8" X 5-1/2" TS ESSION. NU BJ ON C ROKE BACK TO 780 PSI NUD CLEAN ACID, CARP	RACKS. RIH W/4-3/4" BIT + BIT SUB + 3 TRIPLE INHIBITED ACID. TED FROM 7475' UP TO 7275'. RIH W/GR/ CARRIER GUN W/PREM CHARGES & SHOT 1 J TAL 10 HOLES. RU HYDROSTATIC TBG TESTE ST PKR + CHANGE OVER + 2-7/8" SN + 232 CSG & PRESSURED BACKSIDE TO 500 PSI & H I. PUMPED AMAY SPOT ACID @ 3.2 BPM. RYING 20 BALL SEALERS. PUMPED AN AVG O
COMPLETION OPERATION: 05/24/95 INSTALL COMPLETION OPERATION: 05/24/95 INSTALL COMPLETION OPERATION: 05/24/95 INSTALL COMPLETION OPERATION: 05/24/95 INSTALL O5/25/95 RU BJ SERVICES & SPOTTED CCL, LOGGED FROM 8943' PBTD ML TO 0 7400', 7402', 7404", 7409', 7415 & TESTED TO 7500 PSI ABOVE SLIPS MI 2-7/8" TBG TO 7306'. ND BOP. SET TIED ONTO TBG & PRESSURED UP TO 16 CONTINUE TREATMENT OF PERFS BY PUM 3.2 BPM.	HAD 290 JTS 2-7/8" TBG LLEY. PICKLED TBG W/2 200 GALS MUD CLEAN OUTOO @ 3500' W/1000 PSI ', 7417', 7422', 7426' HILE RUNNING IN HOLE W PKR W/20 POINTS COMPR BO PSI, & FORMATION BR PING 750 GALS 7-1/2% W TREE SAVER ON TREE. RFRAC 30# X-LINKED GEI	UNLOADED ONTO PIPE OO GALS 7-1/2" NEFE TACID TRIP. INHIBI ON CSG. RIH W/4" , 7431', 7475'. TOT 1/2-3/8" X 5-1/2" TS ESSION. NU BJ ON C ROKE BACK TO 780 PSI RUD CLEAN ACID, CARF PRESSURED BACKSIDE CARRYING 42,000# 1	E RACKS. RIH W/4-3/4" BIT + BIT SUB + E TRIPLE INHIBITED ACID. TED FROM 7475' UP TO 7275'. RIH W/GR/ CARRIER GUN W/PREM CHARGES & SHOT 1 J TAL 10 HOLES. RU HYDROSTATIC TBG TESTE OF PKR + CHANGE OVER + 2-7/8" SN + 232 CSG & PRESSURED BACKSIDE TO 500 PSI & H I. PUMPED AMAY SPOT ACID @ 3.2 BPM. RYING 20 BALL SEALERS. PUMPED AN AVG OF TO 500 PSI. RU ON TBG TO FRAC PERFS 16/30 OTTAWA + 8,000 16/30 RESIN COATED
COMPLETION OPERATION: 05/24/95 OF THE COMPLETION OPERATION: 05/24/95 OF THE COL, LOGGED FROM 8943' PBTD WIL TO 05/25/95 RU BJ SERVICES & SPOTTED CCL, LOGGED FROM 8943' PBTD WIL TO 07400', 7402', 7404", 7409', 7415 TESTED TO 7500 PSI ABOVE SLIPS WILL 2-7/8" TBG TO 7306'. ND BOP. SET TIED ONTO TBG & PRESSURED UP TO 16 CONTINUE TREATMENT OF PERFS BY PUM 3.2 BPM. 05/30/95 RU BJ SERVICES. INSTALL 7400' TO 7475' W/14,000 GALS SPECT SAND @ RATE OF +/- 8 BPM.	HAD 290 JTS 2-7/8" TBG LLEY. PICKLED TBG W/2 200 GALS MUD CLEAN OUTOO @ 3500' W/1000 PSI ', 7417', 7422', 7426' HILE RUNNING IN HOLE W PKR W/20 POINTS COMPR BO PSI, & FORMATION BR PING 750 GALS 7-1/2% W TREE SAVER ON TREE. RFRAC 30# X-LINKED GEI	UNLOADED ONTO PIPE OO GALS 7-1/2" NEFE TACID TRIP. INHIBI ON CSG. RIH W/4" , 7431', 7475'. TOT 1/2-3/8" X 5-1/2" TS ESSION. NU BJ ON C ROKE BACK TO 780 PSI RUD CLEAN ACID, CARF PRESSURED BACKSIDE CARRYING 42,000# 1	RACKS. RIH W/4-3/4" BIT + BIT SUB + : TRIPLE INHIBITED ACID. TED FROM 7475' UP TO 7275'. RIH W/GR/ CARRIER GUN W/PREM CHARGES & SHOT 1 J TAL 10 HOLES. RU HYDROSTATIC TBG TESTE ST PKR + CHANGE OVER + 2-7/8" SN + 232 CSG & PRESSURED BACKSIDE TO 500 PSI & H I. PUMPED AWAY SPOT ACID @ 3.2 BPM. RYING 20 BALL SEALERS. PUMPED AN AVG O
COMPLETION OPERATION: 05/24/95 OF THE TO 8948 PBTD TBG TAINS 2-7/8" TBG TO 8948 PBTD TBG TAINS 2-7/8" TBG TO 8948 PBTD TBG TAINS 2-7/8" TBG TO 8948 PBTD TBG TAINS 2-7/95 RU BJ SERVICES & SPOTTED CCL, LOGGED FROM 8943 PBTD WL TO 67400', 7402', 7404", 7409', 7415 TESTED TO 7500 PSI ABOVE SLIPS WITH 2-7/8" TBG TO 7306'. ND BOP. SET TIED ONTO TBG & PRESSURED UP TO 16 CONTINUE TREATMENT OF PERFS BY PUM 3.2 BPM. 05/30/95 RU BJ SERVICES. INSTALL 7400' TO 7475' W/14,000 GALS SPECT SAND 6 RATE OF +/- 8 BPM. Chereby cerefy that the information above is true and communication.	HAD 290 JTS 2-7/8" TBG LLEY. PICKLED TBG W/2 200 GALS MUD CLEAN OUTOO @ 3500' W/1000 PSI ', 7417', 7422', 7426' HILE RUNNING IN HOLE W PKR W/20 POINTS COMPR BO PSI, & FORMATION BR PING 750 GALS 7-1/2% W TREE SAVER ON TREE. RFRAC 30# X-LINKED GEI	UNLOADED ONTO PIPE OO GALS 7-1/2" NEFE TACID TRIP. INHIBI ON CSG. RIH W/4" , 7431', 7475'. TOT 1/2-3/8" X 5-1/2" TS ESSION. NU BJ ON C ROKE BACK TO 780 PSI RUD CLEAN ACID, CARF PRESSURED BACKSIDE CARRYING 42,000# 1	E RACKS. RIH W/4-3/4" BIT + BIT SUB + E TRIPLE INHIBITED ACID. TED FROM 7475' UP TO 7275'. RIH W/GR/ CARRIER GUN W/PREM CHARGES & SHOT 1 J TAL 10 HOLES. RU HYDROSTATIC TBG TESTE OF PKR + CHANGE OVER + 2-7/8" SN + 232 CSG & PRESSURED BACKSIDE TO 500 PSI & H I. PUMPED AMAY SPOT ACID @ 3.2 BPM. RYING 20 BALL SEALERS. PUMPED AN AVG OF TO 500 PSI. RU ON TBG TO FRAC PERFS 16/30 OTTAWA + 8,000 16/30 RESIN COATED
COMPLETION OPERATION: 05/24/95 JTS 2-7/8" TBG TO 8948 PBTD TBG TAI 05/25/95 RU BJ SERVICES & SPOTTED CCL, LOGGED FROM 8943 PBTD ML TO 07400', 7402', 7404", 7409', 7415 & TESTED TO 7500 PSI ABOVE SLIPS M 2-7/8" TBG TO 7306'. ND BOP. SET TIED ONTO TBG & PRESSURED UP TO 16 CONTINUE TREATMENT OF PERFS BY PUM 3.2 BPM. 05/30/95 RU BJ SERVICES. INSTALL 7400' TO 7475' W/14,000 GALS SPECT SAND @ RATE OF +/- 8 BPM. [hereby certify that the information above is true and com SIGNATURE DOROTHEA LOGAN TYPE OR PRINT NAME DOROTHEA LOGAN (This space for State Use)	AD 290 JTS 2-7/8" TBG LLEY. PICKLED TBG W/2 200 GALS MUD CLEAN OUTOC @ 3500' W/1000 PSI ', 7417', 7422', 7426' HILE RUNNING IN HOLE W PKR W/20 POINTS COMPR BO PSI, & FORMATION BR PING 750 GALS 7-1/2% W TREE SAVER ON TREE. RFRAC 30# X-LINKED GEI Diede to the best of my knowledge and the company of the c	UNLOADED ONTO PIPE OO GALS 7-1/2" NEFE ON CSG. RIH W/4" , 7431', 7475'. TOT 1/2-3/8" X 5-1/2" TS ESSION. NU BJ ON C OKE BACK TO 780 PSI UD CLEAN ACID, CARP PRESSURED BACKSIDE CARRYING 42,000# 1	RACKS. RIH W/4-3/4" BIT + BIT SUB + TRIPLE INHIBITED ACID. TED FROM 7475' UP TO 7275'. RIH W/GR/ CARRIER GUN W/PREN CHARGES & SHOT 1 J TAL 10 HOLES. RU HYDROSTATIC TBG TESTE OF PKR + CHANGE OVER + 2-7/8" SN + 232 CSG & PRESSURED BACKSIDE TO 500 PSI & H TO PUMPED AMAY SPOT ACID @ 3.2 BPM. RYING 20 BALL SEALERS. PUMPED AN AVG OF TO 500 PSI. RU ON TBG TO FRAC PERFS 16/30 OTTAWA + 8,000 16/30 RESIN COATED ALYST DATE JUNE 6. 1995 TELEPHONE NO.915 684-744
COMPLETION OPERATION: 05/24/95 DISCRIPTION OPERATION: 05/24/95 DISCRIPTION OPERATION: 05/24/95 DISCRIPTION: 05/25/95 RU BJ SERVICES & SPOTTED CCL, LOGGED FROM 8943' PBTD ML TO 07400', 7402', 7404", 7409', 7415 TESTED TO 7500 PSI ABOVE SLIPS ME 2-7/8" TBG TO 7306'. ND BOP. SET TIED ONTO TBG & PRESSURED UP TO 16 CONTINUE TREATMENT OF PERFS BY PUM 3.2 BPM. 05/30/95 RU BJ SERVICES. INSTALL TAOO' TO 7475' M/14,000 GALS SPECT SAND 0 RATE OF +/- 8 BPM. Chereby cerefy that the information above is true and communication above is true and communication.	AD 290 JTS 2-7/8" TBG LLEY. PICKLED TBG W/2 200 GALS MUD CLEAN OUTOC @ 3500' W/1000 PSI ', 7417', 7422', 7426' HILE RUNNING IN HOLE W PKR W/20 POINTS COMPR BO PSI, & FORMATION BR PING 750 GALS 7-1/2% W TREE SAVER ON TREE. RFRAC 30# X-LINKED GEI Diede to the best of my knowledge and the company of the c	UNLOADED ONTO PIPE OO GALS 7-1/2" NEFE TACID TRIP. INHIBI ON CSG. RIH W/4" , 7431', 7475'. TOT 1/2-3/8" X 5-1/2" TS ESSION. NU BJ ON C ROKE BACK TO 780 PSI RUD CLEAN ACID, CARF PRESSURED BACKSIDE CARRYING 42,000# 1	RACKS. RIH W/4-3/4" BIT + BIT SUB + TRIPLE INHIBITED ACID. TED FROM 7475' UP TO 7275'. RIH W/GR/ CARRIER GUN W/PREN CHARGES & SHOT 1 J TAL 10 HOLES. RU HYDROSTATIC TBG TESTE OF PKR + CHANGE OVER + 2-7/8" SN + 232 CSG & PRESSURED BACKSIDE TO 500 PSI & H T. PUMPED AMAY SPOT ACID @ 3.2 BPM. RYING 20 BALL SEALERS. PUMPED AN AVG OF TO 500 PSI. RU ON TBG TO FRAC PERFS 16/30 OTTAWA + 8,000 16/30 RESIN COATED ALYST DATE JUNE 6. 1995 TELEPHONE NO. 915 684-744