

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-86149

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Red Tank 26 Federal No. 4

9. API Well No.

30-025-32386

10. Field and Pool, or Exploratory Area

West Red Tank Delaware

11. County or Parish, State

Lea, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 330' FWL, Sec. 26, T22S, R32E

CONFIDENTIAL

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Intermediate Casing
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 11" hole to 4520'. TD reached @ 0900 hrs CST 3/9/94. Ran 101 jts 8-5/8", 32#, J-55 & S-80, ST&C casing. Float shoe @ 4520'. Casing packer @ 3362'. DV tool @ 3359'. Howco cemented 1st stage w/ 300 sx Premium Plus @ 14.8 ppg. Drop plug & displace cement. Inflate packer. Drop bomb and open DV tool. Cement 2nd stage w/ 1300 sx Halliburton Lite @ 12.7 ppg followed by 50 sx Premium Plus. Plug down @ 2230 hrs CST 3/9/94. Recovered 250 sx excess cement. ND BOP's and make cut-off. Weld on wellhead and test to 2000 psi. NU BOP's and test to 1500 psi.

14. I hereby certify that the foregoing is true and correct

Signed

Title Senior Operations Engineer

Date April 6, 1994

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side