

Form 3160-5  
(June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993  
5. Lease Designation and Serial No  
NM-81272  
6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
Pogo Producing Company

3. Address and Telephone No.  
P. O. Box 10340, Midland, TX 79702-7340

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
660' FNL & 660' FEL, Section 27, T22S, R32E

7. If Unit or CA, Agreement Designation

8. Well Name and No.  
Prize Federal No. 5

9. API Well No.  
30-025-32437

10. Field and Pool, or Exploratory Area  
Red Tank Delaware West

11. County or Parish, State  
Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud & Set Surface Csg  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU Nabors Rig #353. Spud well @ 1700 hrs CST 3/24/94. Drilled 17-1/2" hole to 670'. TD reached @ 1200 hrs CST 3/26/94. Ran 15 jts 13-3/8", 54.5#, J-55, ST&C casing. TPGS @ 670'. IFV @ 624'. Howco cemented casing w/ 650 sx Halliburton Lite @ 12.7 ppg followed by 200 sx Premium Plus @ 14.8 ppg. Plug down @ 1730 hrs CST 3/25/94. Recovered 143 sx excess cement. WOC 11-1/4 hrs. Cement has a compressive strength over 500 psi in 8 hrs. Make cut-off. Weld on wellhead and test to 500 psi. NU BOP's and test to 1000 psi.

J. Lara  
3/1994

14. I hereby certify that the foregoing is true and correct

Signed Barnett Lamb Title Senior Operations Engineer Date May 12, 1994

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_  
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

**RECEIVED**

JUL 24 1995

JCD HOBBS  
OFFICE