

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-32561
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil / Gas Lease No.	B-160
7. Lease Name or Unit Agreement Name	NEW MEXICO 'H' STATE NCT-3
8. Well No.	35
9. Pool Name or Wildcat	EUMONT YATES SEVEN RIVERS QUEEN (PRO GAS)
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3524', KB-3537'	

SUNDRY NOTICES AND REPORTS ON WELL
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.
3. Address of Operator P.O. Box 3109, Midland Texas 79702	9. Pool Name or Wildcat EUMONT YATES SEVEN RIVERS QUEEN (PRO GAS)
4. Well Location Unit Letter <u>E</u> : <u>1880</u> Feet From The <u>NORTH</u> Line and <u>710</u> Feet From The <u>WEST</u> Line Section <u>19</u> Township <u>20-S</u> Range <u>37-E</u> NMPM <u>LEA</u> COUNTY	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3524', KB-3537'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPERATION ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐ PRODUCTION CASING ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLED 7 7/8 HOLE TO 3565'. TD @ 1:00 PM 09-05-94.
2. RAN 56 JOINTS OF 5 1/2, 15.5# CF-50 AND 26 JOINTS OF 15.5# J-55, LTC CASING SET @ 3565'.
3. DOWELL CEMENTED WITH 400 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 300 SACKS 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.35 CF/S). PLUG DOWN @ 7:04 AM 09-09-94. CIRCULATED 96 SACKS.
4. ND. RELEASE RIG @ 12:00 PM 09-09-94.
5. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C. P. Basham / JPH TITLE Drilling Operations Mgr. DATE 9/13/94
TYPE OR PRINT NAME C. P. Basham Telephone No. 688-4608

(This space for State Use) ORIGINAL FILED IN COUNTY SECTOR
APPROVED BY DAVID J. HARRIS TITLE STATE ENGINEER DATE SEP 16 1994
CONDITIONS OF APPROVAL, IF ANY: