## N.M. OIL CONS. COMMISSION P.O. BOX 1980 HOBBS, NEW MEXICO 88240

Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR RURFALL OF LAND MANAGEMENT

FORM APPROVED	
Budget Bureau No. 1004-0135	
Expires: March 31, 1993	

**BUREAU OF LAND MANAGEMENT** 5. Lease Designation and Serial No. LC 031695B SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Gas Well \_ Other 8. Well Name and No. 2. Name of Operator WARREN UNIT DRINKARD #105 Conoco Inc. 9. API Well No. 3. Address and Telephone No. 30-025-32666 10 Desta Drive STE 100W, Midland, TX 79705 (915)686-5424 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) WARREN DRINKARD 11. County or Parish, State 2203 FSL, & 2058 FEL, SEC. 28, T 20S, R 38E, UNIT LTR 'J' LEA. NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other SPUD SET SURFACE CSG Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* 9-26-95 MIRU SPUD 12 1/4" HOLE @ 8pm ON 9-26-94, DRILL TO DEPTH OF 1467. GIH W/ 33 JTS 9-5/8". 26# K-34 STC CSG SET @ 1467. SHOE SET @ 1467. COLLAR SET @ 1421. LEAD SLURRY 500 SX CLASS 'C' W/ 4% BFC + 2% CACL + .2% SMS. TAIL SLURRY 200 SX CLASS 'C' W/ 2% CACL2. DISPLACED W/ 110 bbl FRESH WATER. BUMPED PLUG @ 10:16 am ON 9-28-94 W/ 1437 PSI. CONTINUED DRILLING 8 3/4" HOLE ON 9-30-94. NOTIFIED BLM ON 9-28-94. -21 MH JU 14. I hereby certify that the foregoing is true and correct SR. REGULATORY SPEC 10-7-94 Date (This space for Federal or State office use) Approved by \_\_\_\_\_\_\_\_ if any: Title