

District I  
PO Box 1980, Hobbs, NM 88241-1980  
District II  
PO Drawer DD, Artesia, NM 88211-0719  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico  
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION  
PO Box 2088  
Santa Fe, NM 87504-2088

Form C-101  
Revised February 10, 1994  
Instructions on back  
Submit to Appropriate District Office  
State Lease - 6 Copies  
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address: OXY USA Inc. P.O. Box 50250 Midland, TX 79710		OGRID Number 16696
		API Number 30-025-32702
Property Code 008661	Property Name State N	Well No. 6

<sup>7</sup> Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
K	2	22S	36E		2050	South	2020	West	Lea

<sup>8</sup> Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
<sup>9</sup> Proposed Pool 1 Eumont Yates 7 RVRs Qn (Pro Gas)					<sup>10</sup> Proposed Pool 2				

<sup>11</sup> Work Type Code Drill	<sup>12</sup> Well Type Code Gas	<sup>13</sup> Cable/Rotary Rotary	<sup>14</sup> Lease Type Code State	<sup>15</sup> Ground Level Elevation 3522'
<sup>16</sup> Multiple Single	<sup>17</sup> Proposed Depth 3800'	<sup>18</sup> Formation Yates-7RVRs-Qn	<sup>19</sup> Contractor N/A	<sup>20</sup> Spud Date ASAP

<sup>21</sup> Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
12 1/4"	8 5/8"	24#	400'	260	Surface
7 7/8"	5 1/2"	15.5#	3800'	810	Surface

<sup>22</sup> Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

See other side

Permit Expires 6 Months From Approval  
Date Unless Drilling Underway

<sup>23</sup> I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Printed name:

David Stewart

Title:

Regulatory Analyst

Date:

10/10/94

Phone:

915-685-5717

OIL CONSERVATION DIVISION

Approved by:

ORIGINAL SIGNATURE OF DISTRICT OFFICIAL

Title:

Approval Date:

OCT 13 1994

Expiration Date:

Conditions of Approval:

Attached ☐

Bit Program:	12-1/4"  le to 400'	
	7-7/8" hole to TD	
BOP Program:	0 - 400'	None
	400' - TD	3000# WP pipe and blind rams with choke manifold
Mud Program:	0 - 400'	Drill with a gel/lime slurry. Use paper to control seepage and for sweeps.
	400' - 3300'	Drill with 10# brine water. Circulate through the reserve pit to control solids. Use paper to control seepage and for sweeps.
	3300' - TD	Raise viscosity to 32-34 secs with salt gel. Reduce waterloss to < 15 cc's. Keep pH < 10.
Coring Program:		None planned
Logging Program:		GR-DLL-MSFL-caliper GR-CNL-lithodensity
DST Program:		None planned
Casing Program:	Surface	0 - 400'  8-5/8" 24# K55 S T C
	Production	0 - TD  5-1/2" 15.5# K55 STC (roughcoat 500')
Cement program	Surface	260 sx Class C + 2% CaCl <sub>2</sub> + 1/4 lb/sk cellophane flakes
	Production	Lead 660 sx Class C Light w/15 lb/sk salt + 1/4 lb/sk cellophane flakes
		Tail 150 sx 50/50 Class H/Poz + 2% gel + 3 lb/sk KCl + .3% Halad-9
		Calculate annular volume from caliper log and adjust volumes if necessary.
Wellhead		8-5/8" 3000# WP Larken "Unistack" casing head 5-1/2" x 2-7/8" 3000# WP Larken "Unistack" tubing head
H <sub>2</sub> S safety		While drilling below 2800', protective breathing equipment at 2 sites, wind direction indicator, and automatic H <sub>2</sub> S detection and alarm equipment shall be on location. All contractor and company personnel shall be trained in H <sub>2</sub> S safety in accordance with TRC Rule 36.