

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION
P.O. BOX 1980
MORRIS, NEW MEXICO 88240
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P.O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 1980' FEL, Section 8, T22S, R32E

5. Lease Designation and Serial No.

NM-90586

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Federal 8 No. 1

9. API Well No.

30-025-32709

10. Field and Pool, or Exploratory Area

Undes Red Tank Morrow

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Set Liner
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5" Liner - Drilled 6-1/8" hole to 15,100'. TD reached 2000 hrs CST 5/24/95. Logged w/ Schlumberger. Ran 70 jts 5", 18#, P-110 FL4S casing. Float shoe @ 1,5100'. Top of liner @ 12,285'. Float collar @ 15,015'. Howco cemented liner w/ 350 sxs Cl "H" + 3 pps KCl + .5% H-344 + .5% H-322 @ 16.4 ppg. Plug down w/ 2500 psi 1130 hrs CST 5/27/95. Set liner pkr. Tag cement @ 12,200'. Drill out cement to liner top @ 11,767'. POOH & RIH w/ RTTS packer to 11,550'. Displace 14 ppg mud in drill pipe w/ fresh water. Monitor liner top. No leaks indicated. Release packer and displace fresh water.

14. I hereby certify that the foregoing is true and correct

Signed

Title Division Operations Manager

Date September 6, 1995

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side