

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Bratos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-32746
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B-9652
7. Lease Name or Unit Agreement Name WARREN MCKEE BRINE <15765>
8. Well No. 4
9. Pool name or Wildcat BSW SALADO <96173>

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☐ GAS WELL ☐ OTHER ☒ BRINE WELL	
2. Name of Operator CONOCO INC. <005073>	
3. Address of Operator 10 Desta Drive Ste 100 W. Midland, TX 79705	
4. Well Location Unit Letter <u>N</u> : <u>330</u> Feet From The <u>SOUTH</u> Line and <u>1980</u> Feet From The <u>WEST</u> Line Section <u>2</u> Township <u>20 S</u> Range <u>38 E</u> NMPM <u>LEA</u> County <u></u>	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3568	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: SPUD & SET CSG. ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-23-94 SPUD 12 1/4" HOLE. DRILL TO 415'. GIH W/ 9 JTS 9 5/8" 36# K-55 ST&C CSG SET @ 415'. SHOE SET @ 415'. COLLAR SET @ 369'. LEAD SLURRY 100 SX CLASS 'C' + 4% GEL + 2% CACL2. TAIL SLURRY 100 SX CLASS 'C' + 2% CACL2. DISPLACED W/ 29 bbl FRESH WATER. CEMENT RETURNS OF 10 SX. BUMPED PLUG @ 3:15 am ON 12-24-94 W/ 600 PSI. NOTIFIED NMOCD @ 8 pm ON 12-23-94 WOC FOR 4 HRS. CONTINUE DRILLING 8 3/4" HOLE.

12-28-94 DRILL 8 3/4" HOLE TO DEPTH OF 1645'. GIH W/ 37 JTS 7" 26# K-55 LTC CSG SET @ 1645'. SHOE SET @ 1645'. COLLAR SET @ 1598'. LEAD SLURRY 200 SX CLASS 'C' + 4% GEL + 2% CACLW + .2% SMS. TAIL SLURRY 150 SX CLASS 'C'. DISPLACED W/ 167 bbl FRESH WATER. CEMENT RETURNS OF 60 SX. BUMPED PLUG @ 4:30 am ON 12-28-94. WAIT ON CEMENT FOR 4 HRS. CONTINUE DRILLING 6 1/8" HOLE TO TD AT 2800'. RELEASED RIG @ 4 am ON 12-30-94.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bill R. Keathly TITLE SR. REGULATORY SPEC. DATE 1-4-95
TYPE OR PRINT NAME BILL R. KEATHLY TELEPHONE NO. 915-686-5424

(This space for State Use)

ORIGINAL SIGNED BY
GARY WINK
FIELD REP. II

APPROVED BY _____ TITLE _____ DATE 1-4-95

CONDITIONS OF APPROVAL, IF ANY: