Form 3160-5 (June 1990)

1. Type of Well

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5.	Lease	Design	ation	and	Serial	No.	

6. If Indian, Allottee or Tribe Name

NM - 85937

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

7. If Unit or CA, Agreement Designation

1. Type of Well	PROHIBITION FEDERAL UNIT			
Well Gas Other	8. Well Name and No.			
2. Name of Operator	PROHIBITION FED. UNIT # 5			
MARALO, INC.	9. API Well No.			
3. Address and Telephone No. P.O. BOX 832 MIDLAND, TEXAS 79702	30-025-32759 10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey Descrip	Red Tank - Bone Spring			
22101 FBT 21551 FT GTG 14 F00	11. County or Parish, State			
2310' FNL, 2155' FWL, SEC. 14, T22	LEA , NEW MEXICO			
CHECK APPROPRIATE BOX(s) T	O INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Abandonment	Change of Plans		
	Recompletion	New Construction		
Subsequent Report	Plugging Back	Non-Routine Fracturing		
	Casing Repair	Water Shut-Off		
Final Abandonment Notice	Altering Casing	Conversion to Injection		
	Other	Dispose Water		
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		
13. Describe Proposed or Completed Operations (Clearly state all perti	nent details, and give pertinent dates, including estimated da	te of starting any proposed work. If well is directionally drilled,		

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* 5-17-96 SET CIBP @ 8445' - 25 sxs on top - 8205'

5-17-96 SPOT 20 sxs @ 4774'-4582'

5-21-96 Spot 50 sxs @ 4464'-4128' tagged Pulled 4222' of 5 ½ casing (see attached slugging regent)

5-23-96 Spot 40 sxs @ 1028'-874'

5-23-96 Spot 65 sxs @ 745'-620'

CIRCULATE HOLE WITH 10# MUD INSTALL DRY HOLE MARKER

5-23-96 Spot 40 sxs @ 60'- surface

> Approved as to plugging of the well come. clability under bond is retained until

surface restoration is completed,

14. I hereby certify that the foregoing is true and correct **REGULATORY ANALYST** Title Approved by Conditions of approval, if any: