

PAGE START DATE: 6/16/95
PAGE START TIME: 12:45: 0
DATA FILE: 9

DELTA TIME HRS	DEPTH FEET	TEMPERATURE 'F	COMMENTS
0.000	40.00	81.50	
0.317	1050.00	85.00	BREAK
0.333	1099.00	89.00	
0.350	1153.00	88.50	
0.400	1331.00	98.50	
0.517	1658.00	95.75	
0.550	1757.00	97.50	
0.600	1919.00	96.50	
0.633	2028.00	98.00	
0.667	2142.00	97.75	
0.717	2321.00	100.75	
0.733	2381.00	100.25	
0.750	2444.00	101.50	
0.767	2508.00	100.75	
0.783	2571.00	102.50	
0.817	2700.00	102.00	
0.867	2855.00	105.00	
0.875	2880.00	103.75	
0.900	2955.00	106.25	
0.917	3006.00	105.25	
0.925	3032.00	106.25	
0.950	3111.00	104.25	
0.967	3163.00	106.75	
0.975	3189.00	103.25	
1.033	3378.00	112.50	
1.050	3433.00	105.25	
1.067	3488.00	107.25	
1.083	3543.00	107.00	
1.117	3657.00	110.00	
1.183	3889.00	101.00	
1.250	4121.00	125.75	
1.267	4183.00	124.50	
1.333	4400.00	138.50	
1.350	4450.00	124.75	
1.383	4558.00	120.50	
1.417	4631.00	132.00	M.D.R.

DATE AND TIME CEMENT JOB COMPLETE:

JUNE 16, 1995 @ 6:30 AM

DATE AND TIME SURVEY MADE:

JUNE 16, 1995 @ 12:30 PM

AMOUNT AND TYPE CEMENT USED:

1550 SACKS HALLIBURTON LIGHT, 15# SALT, 1/4#
FLOSEAL; 250 SACKS PREMIUM NEAT RUN BEHIND
4700 FEET OF 8-5/8" CASING IN A 12 1/4" HOLE.

DEPTH FIGURED FROM:

KELLY BUSHING