

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION  
P.O. BOX 1980  
HOBBS, NEW MEXICO 88240

Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

410' FNL & 990' FWL, Section 34, T22S, R32E

5. Lease Designation and Serial No.

NM-77060

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Red Tank 34 Federal No. 13

9. API Well No.

30-025-32761

10. Field and Pool, or Exploratory Area

Red Tank Delaware West

11. County or Parish, State

Lea County, NM

CONFIDENTIAL

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other TD & Production Casing  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled 7-7/8" hole to 8722'. TD reached @ 1245 hrs CST 12/20/94. Logged well w/ Schlumberger. Ran 198 jts 5-1/2", 17#, J-55 & L-80 LT&C casing. Float shoe @ 8722'. Float collar @ 8675'. Stage tool @ 6613'. Howco cemented 1st stage w/ 410 sx Class "H" + 5 pps Microbond + 2.4 pps KCl + .6% H-322 @ 15.6 ppg. Displace cement and land plug. Drop bomb and open DV tool. Circulated 4 hrs between stages. Recovered 69 sxs excess cement. Cement 2nd stage w/ 800 sxs Class "C" + 12 pps Gilsonite + 2.8 pps KCl + .3% Halad 332 + .3% Halad 344 @ 14.1 ppg. Plug down @ 0845 hrs CST 12/22/94. TOC @ 3096'. ND BOP's and make cut-off. Weld on wellhead and test to 2500 psi.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Senior Operations Engineer Date Jan. 4, 1995

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_  
Conditions of approval, if any: \_\_\_\_\_

FOR RECORD

[Signature]  
JAN - 6 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

CARLSBAD, NEW MEXICO

the 1990s, the number of people in the world who are under 15 years of age is expected to increase from 1.1 billion to 1.5 billion. The number of people aged 65 and over is expected to increase from 200 million to 400 million. The number of people aged 15 and over is expected to increase from 3.5 billion to 4.5 billion. The number of people aged 15 and over is expected to increase from 3.5 billion to 4.5 billion. The number of people aged 15 and over is expected to increase from 3.5 billion to 4.5 billion.

FEB 1968  
 Received  
 HODGS  
 000